

10.2 Arrays

Name: _____ Class: _____ Date: _____ **Total: 35 marks**

KEY WORDS bounds • linear search • index • element • arrays

Objective

An **array** lets a weather station store, search and process many readings using loops.

Learn: declarations, bounds, tracing, totals, counts, searching and array processing. Continue with **10.2.1** for bubble sort and insertion/deletion, then **10.2.2** for combined exam practice.


1 Key knowledge and worked examples

■ Elements, indices and bounds

An array holds a fixed number of same-type **elements**, each reached by an integer **index**. **Lower bound** and **upper bound** are the first and last valid indices, both included. A **dimension** is one indexing direction.

```
DECLARE Scores : ARRAY[0:4] OF INTEGER
Scores[3] ← 75
```

Scores[3] is the fourth element; Scores[5] is invalid. Number of elements = upper bound – lower bound + 1, so this array holds 4 – 0 + 1 = 5 elements. Indices need not start at 1.



Use **1-D** for a sequence; **2-D** for two directions, such as month and shop. Declare all bounds and the type. Declaration does not initialise values.

■ Initialise, input, total and count

Worked example: enter five marks, output the mean and count marks at least 50. Replace INPUT Mark[Index] with Mark[Index] ← 0 to initialise elements.

```
DECLARE Mark : ARRAY[1:5] OF INTEGER
DECLARE Index, Total, PassCount : INTEGER
Total ← 0
PassCount ← 0
FOR Index ← 1 TO 5
    INPUT Mark[Index]
    Total ← Total + Mark[Index]
    IF Mark[Index] >= 50 THEN
        PassCount ← PassCount + 1
    ENDIF
NEXT Index
OUTPUT "Mean: ", Total / 5, ", passes: ", PassCount
```

For 40, 50, 70, 20, 80: total 260, mean 52, count 3. A total adds **values**; a count adds **one**. Initialise before the loop; output afterwards. Trace updates in statement order.

■ Largest value and its position

For non-empty integer array A[1:n], start with its first value. Starting at zero fails for all-negative data.

```
DECLARE Index, Largest, Position : INTEGER
Largest ← A[1]
Position ← 1
FOR Index ← 2 TO n
    IF A[Index] > Largest THEN
        Largest ← A[Index]
        Position ← Index
    ENDIF
NEXT Index
OUTPUT "Largest: ", Largest, ", index: ", Position
```

For -8, -2, -2, -5, the maximum is -2 at index 2. > keeps the first tie; >= keeps the last. Reverse the comparison for a minimum.

■ Two dimensions: rows, columns and totals

		column index				
		1	2	3	4	
row index	1					
	2			99		← Grid[2,3] ← 99
	3					

```
DECLARE Grid : ARRAY[1:3, 1:4] OF INTEGER
Grid[2, 3] ← 99
```

There are $3 \times 4 = 12$ elements. Here the first index is row, the second column; follow the question's convention.

Worked example: Grid is filled. Output each row total and the whole-grid total.

```
DECLARE Row, Col, RowTotal, GrandTotal : INTEGER
GrandTotal ← 0
FOR Row ← 1 TO 3
  RowTotal ← 0
  FOR Col ← 1 TO 4
    RowTotal ← RowTotal + Grid[Row, Col]
  NEXT Col
  OUTPUT "Row ", Row, ": ", RowTotal
  GrandTotal ← GrandTotal + RowTotal
NEXT Row
OUTPUT GrandTotal
```

Reset RowTotal per row. For column totals, put columns in the outer loop. For one row, fix the row index and loop over columns.

■ Linear search: return the first match

A **linear search** checks in order. This function uses global integer array A[1:n], with $n \geq 1$. A function returns a value; a procedure has no return value.

```
FUNCTION FindFirst(Target : INTEGER) RETURNS INTEGER
  DECLARE Index, FoundAt : INTEGER
  Index ← 1
  FoundAt ← -1
  WHILE Index <= n AND FoundAt = -1
    IF A[Index] = Target THEN
      FoundAt ← Index
    ENDIF
    Index ← Index + 1
  ENDWHILE
  RETURN FoundAt
ENDFUNCTION
```

For 4, 7, 7, 2, searching for 7 returns 2; 9 returns -1. Stop at the first match. Both 0 and -1 could mean failure here: choose a value outside the **declared** bounds.

■ Capacity and used elements

Capacity is the number allocated; **Count** is the number used. In Data[1:20] with Count = 3, process only 1:3. Before adding, check Count < 20, increment it, then assign Data[Count].

2 Practice

Now apply the methods above.

2.1 Explain the array terms **element** and **bounds**. [2]

1	2	3	4	5	6

2.2 Declare a 1-D array **Scores** of **10** integers, then set the **4th** element to **75**. [2]

Scores										
	1	2	3	4	5	6	7	8	9	10

2.3 Write a FOR loop to output **all 10** elements of **Scores**. [2]

Scores

12345678910

2.4 A cinema has **5** rows and **8** seats per row, each marked 'F' (free) or 'X' (taken). Declare a suitable **2-D** array **Seats**. [2]

screen

X

X

X

X

X

X

3 Exam-style questions

3.1 Array **Temps**[1:n] holds **n** real temperatures, where **n** >= 1. Write pseudocode to find and output the **largest** value. [4]

Temps

21.5

19.0

23.4

...

20.2

123n

3.2 Write pseudocode for a **linear search** of **IDs**[1:n] for a value **Wanted**. Output the position of the **first** match, or "Not found" if it is absent. Assume **n** >= 1; stop searching once a match is found. [4]

IDs

...

123n

Wanted

3.3 Global array **Sales**[1:12, 1:4] contains real monthly sales. Row = month; column = shop. Write pseudocode to output the annual total for **each** shop and the number of months in which that shop's sales were above 10000. Declare local variables. [6]

shop 1 to 4

month 1 to 12

Sales

3.4 A weather station stores the last 24 hourly temperature readings in a 1D array **Reading** of type **REAL**, indexed from 1 to 24.

(a) **Complete** procedure **Store()**, which inputs 24 real readings and stores them in consecutive array elements. [5]

```
PROCEDURE Store()
  DECLARE Index : .....
  FOR Index ← 1 TO .....
    ..... Reading[.....]
    ..... Index
  ENDPROCEDURE
```

(b) Explain why a running maximum should start at **Reading[1]** rather than 0. [1]

 Reading

			...	
1	2	3		24

(c) A function **FindFirstAbove(Limit)** returns the **index** of the first reading above **Limit**, or **−1** if there is none. Explain why **−1** is suitable for “not found”, and whether 0 would also be suitable for this declaration. [2]

(d) **Write** pseudocode for the function **FindFirstAbove()**, which takes the real parameter **Limit**. Stop searching as soon as a reading above **Limit** is found. [5]

Solutions

Each answer shows the steps, then the **result**.

2.1

- **element** – one item stored in the array
- **bounds** – the lowest and highest valid index values

2.2

- declare the array, then assign one element

```
DECLARE Scores : ARRAY[1:10] OF INTEGER
Scores[4] ← 75
```

- also accept ARRAY[0:9] with Scores[3] ← 75: the 4th element follows from the lower bound

2.3

- loop from 1 to 10 and output each element

```
FOR i ← 1 TO 10
    OUTPUT Scores[i]
NEXT i
```

- for ARRAY[0:9], loop FOR i ← 0 TO 9; the loop bounds must match the declared bounds

2.4

- 2-D ARRAY[..., ...] of CHAR
- DECLARE Seats : ARRAY[1:5, 1:8] OF CHAR

3.1

- initialise Max to the first element, then scan the rest

```
DECLARE i : INTEGER
DECLARE Max : REAL
Max ← Temps[1]
FOR i ← 2 TO n
    IF Temps[i] > Max THEN
        Max ← Temps[i]
    ENDIF
NEXT i
OUTPUT Max
```

- compare + update; OUTPUT after the loop

3.2

- initialise index and failure value; bounded conditional loop; compare and keep first position; output found/not found after loop.

```
DECLARE Index, FoundAt : INTEGER
Index ← 1
FoundAt ← -1
WHILE Index <= n AND FoundAt = -1
    IF IDs[Index] = Wanted THEN
        FoundAt ← Index
    ENDIF
    Index ← Index + 1
ENDWHILE
IF FoundAt = -1 THEN
    OUTPUT "Not found"
ELSE
    OUTPUT FoundAt
ENDIF
```

3.3

- local declarations; outer loop for shops; reset totals/counts per shop; inner loop over months; total and conditional count; output each shop's results after its month loop.

```
DECLARE Shop, Month, Count : INTEGER
DECLARE Total : REAL
FOR Shop ← 1 TO 4
    Total ← 0
    Count ← 0
    FOR Month ← 1 TO 12
        Total ← Total + Sales[Month, Shop]
        IF Sales[Month, Shop] > 10000 THEN
            Count ← Count + 1
        ENDIF
    NEXT Month
    OUTPUT "Shop ", Shop, ": ", Total, ", months: ", Count
NEXT Shop
```

3.4

(a) INTEGER; 24; INPUT; Index; NEXT.

(b) all readings could be negative, so starting at zero could output a value that is not in the array.

(c)

- valid indices are 1 to 24, so −1 cannot be confused with a matching index
- 0 would also work for this declaration, because it is outside these bounds; it would not work if 0 were a valid index

(d)

```
FUNCTION FindFirstAbove(Limit : REAL) RETURNS INTEGER
  DECLARE FoundAt, Index : INTEGER
  FoundAt ← -1
  Index ← 1
  WHILE Index <= 24 AND FoundAt = -1
    IF Reading[Index] > Limit THEN
      FoundAt ← Index
    ELSE
      Index ← Index + 1
    ENDIF
  ENDWHILE
  RETURN FoundAt
ENDFUNCTION
```

- header with parameter and return type; `FoundAt` initialised to `-1`; loop with both conditions; correct comparison; `RETURN`