

11 Programming – Part 2

Name: _____ Class: _____ Date: _____

Vocabulary

Write each word three times.

English	Write it 3 times (English)
operators	_____
library routines	_____
concatenation	_____
nested	_____

Recall


In **Part 1** you used variables and constants, the three constructs (selection, iteration), arrays, and subroutines (procedures, functions, parameters, scope). Part 2 adds two more operators and ready-made functions, the **CASE** statement, and writing clean, efficient code.

New ideas

Read these first. Each idea has a short worked example. Then do the Practice.

■ 1 Operators and library routines

Besides $+$ $-$ $\times$ $\div$, two useful **operators** work on whole numbers: **DIV** (integer division – $7 \text{ DIV } 2 = 3$) and **MOD** (the remainder – $7 \text{ MOD } 2 = 1$).




Many jobs already have ready-made **library routines**, so you don't write them yourself – string functions like `LENGTH(s)`, `LEFT(s, n)`, `MID(s, start, len)`, and joining two strings (**concatenation**) with `&`.

Worked example. `23 DIV 10 = 2` and `23 MOD 10 = 3`, so 23 is "2 tens and 3 ones"; `LEFT("HELLO", 2)` gives "HE".

■ 2 The CASE statement

To test one value against many options, a deep **nested IF** is hard to read; a **CASE** is cleaner:



```

CASE OF grade
  "A": OUTPUT "Excellent"
  "B": OUTPUT "Good"
  OTHERWISE: OUTPUT "Try again"
ENDCASE
  
```

Worked example. With `grade = "B"`, the CASE above matches the "B" branch and outputs "Good".

■ 3 Writing efficient, readable code

- compute a value **once before a loop** if it doesn't change inside it;
- **exit a loop early** when the answer is found;
- use **meaningful names** (`numberOfPupils`, not `n`) and comment the *intent*, not the mechanics.

slower

```
FOR i = 1 TO n
  x = slow() // every pass
  use(x, i)
NEXT i
```

faster

```
x = slow() // once
FOR i = 1 TO n
  use(x, i)
NEXT i
```

Worked example. If a loop runs `tax ← price * 0.2` every pass but `price` never changes inside it, move that line above the loop so it runs once, not a thousand times.

Watch out: DIV throws away the remainder – 7 DIV 2 is 3, not 3.5. Use MOD when you want the remainder.

Practice

11.1 Find (a) 17 DIV 5 and (b) 17 MOD 5. [2]

11.2 Find (a) LENGTH("HELLO") and (b) LEFT("HELLO", 2). [2]

11.3 State when a CASE statement is a better choice than a nested IF. [1]

11.4 State the condition (using MOD) that is true when n is even. [1]

11.5 State one way to make a loop run more efficiently. [1]

11.6 Explain *why* `n MOD 2 = 0` is a correct test for whether n is even. [2]

11.7 Challenge. Using `DIV` and `MOD`, write pseudocode that inputs a number of seconds and outputs the whole minutes and the leftover seconds. [3]