

A-Level Computer Science

Name: _____ Score: _____

1. How many bits does one hexadecimal digit represent?

- ☐ 16
- ☐ 1
- ☐ 4
- ☐ 8

2. Add the binary numbers '0101' + '0011'. Give the 4-bit result.

3. A character set such as ASCII defines:

- ☐ a numeric code point for each character
- ☐ the speed of the processor
- ☐ how files are compressed
- ☐ the colour of each pixel

4. The colour depth (bit depth) of a bitmap image is:

- ☐ how much the file is compressed
- ☐ the number of pixels across the image
- ☐ the physical size of the screen
- ☐ the number of bits used to store each pixel

5. What does sampling do?

- ☐ makes the sound louder
- ☐ converts digital data into analogue data
- ☐ removes frequencies the ear cannot hear
- ☐ measures the amplitude of an analogue wave at regular intervals and stores each as a binary number

6. Lossless compression means:

- ☐ the data is encrypted
- ☐ some detail is permanently lost
- ☐ the file gets bigger
- ☐ the exact original data can be recovered

7. How many bits are in one byte?

_____ bits

8. What is the 4-bit two's complement of '0011'? (invert, then add 1)

9. How many different code points does 7-bit ASCII have?

10. How many bits of colour depth are needed to store 256 different colours?

_____ bits

1. **4**

One hex digit (0–F) covers 16 values = 2^4 , so it maps to exactly 4 bits (a nibble).

2. **1000**

$5 + 3 = 8$, which is ‘1000’ in binary.

3. **a numeric code point for each character**

A character set maps each character to a number (its code point), which is what the computer actually stores.

4. **the number of bits used to store each pixel**

Colour depth is bits per pixel – more bits means more possible colours (8 bits → 256, 24 bits → 16.7 million).

5. **measures the amplitude of an analogue wave at regular intervals and stores each as a binary number**

Sampling turns a continuous analogue wave into discrete digital values. Removing inaudible frequencies is lossy compression, a different step.

6. **the exact original data can be recovered**

Lossless compression lets you rebuild the original data exactly – essential for text, programs and ZIP/PNG.

7. **8 bits**

A byte is 8 bits (and a nibble is 4 bits).

8. **1101**

Invert ‘0011’ → ‘1100’, then add 1 → ‘1101’ (which represents -3).

9. **128**

7 bits give $2^7 = 128$ code points.

10. **8 bits**

$2^8 = 256$, so 8 bits per pixel give 256 colours.