

19. Computational thinking and Problem-solving

Starter Quiz ·

A-Level Computer Science

Name: _____ Score: _____

1. A linear search:

- ☐ checks each element in turn and works on any list
- ☐ always finds the target in one step
- ☐ requires the data to be sorted
- ☐ only works on numbers

2. Bubble sort works by:

- ☐ repeatedly swapping adjacent out-of-order pairs
- ☐ building a binary tree
- ☐ halving the list each time
- ☐ inserting each element into a sorted prefix

3. Which Big-O describes binary search?

- ☐ $O(n)$
- ☐ $O(n^2)$
- ☐ $O(n \log n)$
- ☐ $O(\log n)$

4. Every recursive algorithm must have a base case because:

- ☐ the compiler requires a comment
- ☐ without it the recursion never stops
- ☐ it speeds up the program
- ☐ it makes the code shorter

5. Linear search is the better choice when the data is:

- ☐ very large and sorted
- ☐ unsorted or only a small list
- ☐ in a database index
- ☐ already a binary tree

6. After the first pass of a bubble sort on 5, 3, 8, 1, what is the array? Write the four numbers separated by commas.

7. An $O(n^2)$ algorithm takes 4 seconds on 1,000 items. Roughly how many seconds will it take on 2,000?

8. Recursion is a natural fit for self-similar problems (trees, divide-and-conquer), but each call adds a stack frame – so without a base case it overflows the stack.

☐ True ☐ False

9. About how many comparisons does a binary search need for one million sorted items?

10. Insertion sort runs close to $O(n)$ on small or nearly-sorted arrays, because few elements need to be shifted.

☐ True ☐ False

1. checks each element in turn and works on any list

Linear search needs no preparation and works on any list, at worst $O(n)$.

2. repeatedly swapping adjacent out-of-order pairs

Each pass swaps adjacent pairs, "bubbling" the largest element to the end.

3. $O(\log n)$

Halving the range each step is logarithmic – $O(\log n)$.

4. without it the recursion never stops

The base case is the condition that ends the chain of calls; without it the recursion runs forever.

5. unsorted or only a small list

With no order to exploit (or a tiny list), linear search avoids the cost of sorting first.

6. 3, 5, 1, 8

5 and 3 swap, 5 and 8 do not, 8 and 1 swap. The largest value has reached the end, so the next pass can be one comparison shorter.

7. 16

Doubling n quadruples an $O(n^2)$ time. The same doubling would take an $O(n)$ algorithm from 4 seconds to 8.

8. True

A simple counting loop is cleaner for plain iteration; recursion shines when the problem contains smaller copies of itself.

9. 20

$\log_2(1\,000\,000) \approx 20$ – about 20 comparisons.

10. True

On nearly-sorted data each new item is already almost in place – which is why insertion sort beats fancier sorts on small inputs.