

Solutions

Each answer shows the steps, then the **result**.

2.1

- a **compiler** translates the **whole** program to machine code first (producing an executable)
- an **interpreter** translates and **runs each statement** as it goes (no executable)

2.2

- **lexical analysis** → **syntax analysis (parsing)** → **semantic analysis**

2.3

- **tokens** (keywords, identifiers, operators, literals)

2.4

- 3 4 +

3.1

- any four: it reads a statement, does **lexical** then **syntax** analysis
- checks it / its types
- **executes** the statement's action immediately
- reports any error at once and usually stops
- repeats for each statement – no executable is produced – max 4

3.2

- `<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9`

3.3

- 3 4 + for the bracket
- 2 * last: 3 4 + 2 *

3.4

- push 5, push 2; - → pop 2 and 5, $5 - 2 = 3$, push 3
- push 3 (stack 3, 3)
- * → $3 \times 3 = 9$, result **9**

3.5

- to make the object (machine) code run **faster** and/or use **less memory**, without changing the result it produces

3.6 any three:

- **whitespace** and **comments** are removed
- the code is split into **tokens** / each lexeme is identified

- **identifiers** are added to the **symbol table**
- keywords and operators are replaced by tokens / lexical errors such as invalid identifiers are reported

3.7 any three:

- the tokens are checked against the **grammar** / **syntax rules** of the language
- a **parse tree** is built from the tokens
- **syntax errors** are found and **reported**
- the output is passed on to code generation / semantic analysis

3.8

(a)

- 8 2 - and 5 9 + for the two brackets
- 8 2 - 5 9 + * 7 /

(b)

- a b * is a * b; c d - is c - d
- a * b + (c - d)

(c)

- push 4, 3, 6; * gives $3 \times 6 = 18$: stack 4, 18
- + gives $4 + 18 = 22$: stack 22
- push 15, 4; - gives $15 - 4 = 11$: stack 22, 11
- / gives $22/11 = 2$

(d)

- 4 is not a `<digit>`: a `<digit>` can only be 1, 2 or 3