

Solutions

Each answer shows the steps, then the **result**.

2.1

- the **simplest case**, solved **directly without** another recursive call – it **stops** the recursion

2.2

- reduces** the input and **calls the function again** (on the smaller problem)

2.3

- the recursion **never stops** – it runs until the **call stack overflows** and the program crashes

2.4

- any two: the **parameters**; the **local variables**; the **return address**

3.1

- a technique where a function **calls itself**
- with a **smaller version** of the problem until a **base case** is reached

3.2

- Factorial(1) returns **1**; Factorial(2) returns **2**; Factorial(3) returns **6**; Factorial(4) returns **24**

3.3

- a new **stack frame** is **pushed**, holding that call's parameters, local variables and return address
- the call runs, and on return its **value is passed back** and the frame is **popped**
- execution resumes at the **return address** in the caller

3.4

- feature: the problem is **self-similar** / can be broken into smaller versions of itself
- example: traversing a **tree**, binary search, merge sort, factorial/Fibonacci

3.5

- advantage: **shorter, clearer** code for self-similar problems
- disadvantage: it uses **more memory** (a stack frame per call) and can cause a **stack overflow**, and is often slower

3.6

(a)

Index	Target	[1]	[2]	[3]	[4]	[5]	[6]	[7]
1	12	4	9	12	18	25	30	0
2	12							
3	12			18				
4	12				25			
5	12					30		
6	12						0	
7	12							

- Index** and **Target** correct throughout
- [1] and [2] unchanged, because 4 and 9 are less than 12
- [3] becomes 18
- [4] becomes 25 and [5] becomes 30
- [6] becomes 0; at Index 7, Numbers[7] is 0, so the recursion **ends**

(b)

- it **deletes** the first value that is **greater than or equal to Target** (here 12), moving the later values **left** to close the gap

(c)

- no element is 0, so the **base case is never reached** before the end of the array
- Numbers[Index + 1] is read **beyond the upper bound**: an **index out of range** error / the recursion would not stop

3.7

(a)

```
FUNCTION SumScores(N : INTEGER) RETURNS INTEGER
    IF N = 0 THEN
        RETURN 0
    ELSE
        RETURN Scores[N] + SumScores(N - 1)
    ENDIF
ENDFUNCTION
```

- function header with parameter N and RETURNS INTEGER
- base case: IF N = 0 THEN RETURN 0
- recursive call with N - 1
- adds Scores[N] to the value returned

(b)

- 4 frames**: SumScores(3), SumScores(2), SumScores(1) and SumScores(0)

- each call **waits** on the stack until the call it made returns, so all four exist when the base case runs