

Exercise walk-through

1.9

Method Signatures

AP Computer Science A

Documentation with Comments

Comments are ignored by the compiler but explain code to people.

Three comment styles

```
// a single-line comment
/* a block comment that
   may span several lines */
/** Returns the larger of a and b. */
int max(int a, int b)
```

A `/** ... */` **Javadoc** comment documents a method's purpose, parameters and return value, including its preconditions and postconditions.

Class methods, instance methods, and where code comes from

class (static) method

belongs to the [class itself](#), so you call it on the class name:
`Math.abs(x)`. [No object needed](#)

instance method

belongs to an [object](#), so you call it on a reference: `s.length()`

a library

pre-written classes you can use; Java's is the [API](#)

compiled


Java source is compiled once to bytecode, then run – so syntax errors surface [before](#) the program starts

abstraction

using a method by its name and contract, without knowing how it works inside

If you find yourself creating an object just to call a method on it, check whether the method is `static` – `Math.sqrt` on a new `Math()` does not compile.

Methods, the API & the Math class, in detail



A class diagram: private attributes and public methods

Exercises 2.1-2.3

2.1 For `public static boolean inRange(int n, int low, int high)`, state the method name, return type and number of parameters. [2]

2.2 Write a call to `inRange` that stores in `ok` whether 15 is between 10 and 20. [1]

2.3 Explain why `int r = twice(2.5);` does not compile. [2]

Exercises 2.1-2.3

2.1 For `public static boolean inRange(int n, int low, int high)`, state the method name, return type and number of parameters. [2]

2.1

- name `inRange`, return type `boolean`
- **3** parameters

2.2 Write a call to `inRange` that stores in `ok` whether 15 is between 10 and 20. [1]

2.2

- `boolean ok = inRange(15, 10, 20);`

2.3 Explain why `int r = twice(2.5);` does not compile. [2]

2.3

- 2.5 runs the `double` version, which returns a `double`
- a `double` cannot be stored in an `int`

Exercises 3.1-3.2

3.1 `public static void greet(String name, int times)`. Which call compiles? [1]

☐

A `greet(3, "Ana");`

B `String g = greet("Ana", 3);`

C `greet("Ana", 3);`

D `greet("Ana");`

3.2 Which pair of headers can **not** both be in one class?

[1]

☐

A `void f(int a)` and `void f(double a)`

B `void f(int a)` and `void f(int a, int b)`

C `int f(int a)` and `double f(int a)`

D `void f(String s)` and `void f(int a)`

Exercises 3.1-3.2

3.1 `public static void greet(String name, int times)`. Which call compiles? [1]

- ☐ A `greet(3, "Ana");`
☐ B `String g = greet("Ana", 3);`
☐ C `greet("Ana", 3);`
☐ D `greet("Ana");`

3.1 C

- right number, order and types; B stores a `void` result

3.2 Which pair of headers can **not** both be in one class? [1]

- ☐ A `void f(int a)` and `void f(double a)`
☐ B `void f(int a)` and `void f(int a, int b)`
☐ C `int f(int a)` and `double f(int a)`
☐ D `void f(String s)` and `void f(int a)`

3.2 C

- same parameter list; the return type alone does not tell them apart

Exercise 3.3

3.3 What is printed by `System.out.println(twice(twice(3)));`?

[1]

☐

A 6

B 12

C 33

D 12.0

Exercise 3.3

3.3 What is printed by `System.out.println(twice(twice(3)));`?

[1]

☐

A 6

B 12

C 33

D 12.0

3.3 B

- `twice(3)` is 6; `twice(6)` is 12, an `int`

Exercise 3.4 (a)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(a) Write a statement that stores the volume of a cylinder of radius 2 and height 5 in v. [1]

Exercise 3.4 (a)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(a) Write a statement that stores the volume of a cylinder of radius 2 and height 5 in v. [1]

(a)

- `double v = volume(2.0, 5.0);`

Exercise 3.4 (b)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(b) Write a statement that calls `report` for a sphere of radius 3, using `volume` as an argument. [2]

Exercise 3.4 (b)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(b) Write a statement that calls `report` for a sphere of radius 3, using `volume` as an argument. [2]

(b)

- `report("sphere", volume(3.0));`

Exercise 3.4 (c)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(c) Explain how Java decides which `volume` method to run for each call.

[2]

Exercise 3.4 (c)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(c) Explain how Java decides which `volume` method to run for each call.

[2]

(c)

- by the number of arguments (and their types)
- one argument matches `volume(double)`; two match `volume(double, double)`

Exercise 3.4 (d)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(d) Explain why `double x = report("cube", 8.0);` does not compile.

[1]

Exercise 3.4 (d)

3.4 A class has these methods:

```
public static double volume(double r)           // a sphere
public static double volume(double r, double h) // a cylinder
public static void report(String shape, double v)
```

(d) Explain why `double x = report("cube", 8.0);` does not compile. [1]

(d)

- `report` is void: it returns no value to store