

Exercise walk-through

4.7

Wrapper Classes

AP Computer Science A

The five standard array algorithms

sum or average

an accumulator declared outside the loop; divide by `length` at the end

max or min

start from `arr[0]`, not from zero – an array of negatives has no element above zero

count matching

a counter, incremented only when the element passes the test

check for a duplicate

a **nested** loop, with the inner one starting at `i+1` so no pair is checked twice

reverse or copy

build into a **new** array, or swap ends inward for an in-place reverse

Every one of these is a traversal plus a small body. Recognising which one a question wants is most of the work.

Why a data structure at all

the problem

a single variable holds **one** value; real problems need many related values – a class roster, pixels, sensor readings

a data structure

holds many values under one name, reached by **index**

an array

fixed length, set when it is created, and `arr.length` is a field, not a method

the bounds

valid indices run 0 to `length-1`; anything outside throws an `ArrayIndexOutOfBoundsException`

the run-time cost

reaching any element takes the same time whatever the index – that is the point of an array

Off-by-one at the top end is the classic array bug: `i <= arr.length` throws, `i < arr.length` does not.

Removing from a list while looping over it

the problem

`remove(i)` shifts every later element down, so the element after the removed one is skipped

fix one

loop backwards, from `size()-1` down to 0 – later shifts cannot affect indices you have passed

fix two

do not increment `i` after a removal, so the next pass re-examines the same index

never

remove inside an enhanced for loop – it throws a `ConcurrentModificationException`

the rest

the array algorithms carry over unchanged, plus insertion and deletion, which arrays cannot do easily

This is the single most-tested ArrayList point. If a question removes items in a loop, it is testing exactly this.

Exercises 2.1-2.3

2.1 Explain why `ArrayList<int>` does not compile.

[1]

2.2 State whether autoboxing or unboxing happens in `double d = prices.get(2);`, where `prices` is an `ArrayList<Double>`.

[1]

2.3 State the value of `Integer.parseInt("12") + Integer.parseInt("3")` and of `"12" + "3"`.

[2]

Exercises 2.1-2.3

2.1 Explain why `ArrayList<int>` does not compile.

[1]

2.1

- an `ArrayList` holds **objects** only; the type must be the wrapper, `Integer`

2.2 State whether autoboxing or unboxing happens in `double d = prices.get(2);`, where `prices` is an `ArrayList<Double>`.

[1]

2.2

- **unboxing**: the `Double` from `get` becomes a `double`

2.3 State the value of `Integer.parseInt("12") + Integer.parseInt("3")` and of `"12" + "3"`.

[2]

2.3

- `12 + 3 = 15`
- string concatenation: `"123"`

Exercises 2.4-3.1

2.4 State the value of `Integer.MIN_VALUE - 1`.

[1]

3.1 Which statement causes **unboxing**?

[1]

☐

A `Integer x = 4;`

B `list.add(10);`

C `int y = list.get(1);`

D `Double z = 2.5;`

Exercises 2.4-3.1

2.4 State the value of `Integer.MIN_VALUE` - 1.

[1]

2.4

- it overflows to `Integer.MAX_VALUE`, $2^{31} - 1$

3.1 Which statement causes **unboxing**?

[1]

☐

A `Integer x = 4;`

B `list.add(10);`

C `int y = list.get(1);`

D `Double z = 2.5;`

3.1 C

- `get` returns an `Integer`, stored in an `int`

Exercise 3.2

3.2 `nums` is an `ArrayList<Integer>` holding `[3, null, 8]`. What happens? [1]

```
int total = 0;  
for (Integer n : nums) total += n;
```

☐

A total is 11

B total is 3

C a `NullPointerException` is thrown

D it does not compile

Exercise 3.2

3.2 `nums` is an `ArrayList<Integer>` holding `[3, null, 8]`. What happens? [1]

```
int total = 0;
for (Integer n : nums) total += n;
```

☐

A total is 11

B total is 3

C a `NullPointerException` is thrown

D it does not compile

3.2 C

- `total += n` unboxes `null`

Exercise 3.3

3.3 `best` should hold the largest value of `int[] arr`, which may hold only negative numbers. Which start value is always correct? [1]

☐

A `int best = 0;`

B `int best = Integer.MIN_VALUE;`

C `int best = Integer.MAX_VALUE;`

D `int best = -1;`

Exercise 3.3

3.3 `best` should hold the largest value of `int[] arr`, which may hold only negative numbers. Which start value is always correct? [1]

☐

A `int best = 0;`

B `int best = Integer.MIN_VALUE;`

C `int best = Integer.MAX_VALUE;`

D `int best = -1;`

3.3 B

- 0 and -1 are larger than every value of an all-negative array

Exercise 3.4 (a)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` typed, such as `["12", "7", "30"]`.

(a) Write a code segment that builds `ArrayList<Integer>` values from typed, converting each `String` with `Integer.parseInt`. [3]

Exercise 3.4 (a)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` `typed`, such as `["12", "7", "30"]`.

(a) Write a code segment that builds `ArrayList<Integer>` values from `typed`, converting each `String` with `Integer.parseInt`. [3]

(a)

```
ArrayList<Integer> values = new ArrayList<Integer>();  
for (String s : typed)  
{  
    values.add(Integer.parseInt(s));  
}
```

- creates an empty `ArrayList<Integer>`
- traverses every `String` in `typed`
- adds `Integer.parseInt(s)` for each

Exercise 3.4 (b)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` typed, such as `["12", "7", "30"]`.

(b) Identify where autoboxing happens in your code.

[1]

Exercise 3.4 (b)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` typed, such as `["12", "7", "30"]`.

(b) Identify where autoboxing happens in your code.

[1]

(b)

- in `values.add(...)`: the `int` from `parseInt` is boxed to an `Integer`

Exercise 3.4 (c)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` typed, such as `["12", "7", "30"]`.

(c) Write a code segment that finds the **smallest** value in `values`, starting from `Integer.MAX_VALUE`. [3]

Exercise 3.4 (c)

3.4 A quiz app stores answers typed by players as `Strings` in `ArrayList<String>` typed, such as `["12", "7", "30"]`.

(c) Write a code segment that finds the **smallest** value in `values`, starting from `Integer.MAX_VALUE`. [3]

(c)

```
int smallest = Integer.MAX_VALUE;
for (int v : values)
{
    if (v < smallest) smallest = v;
}
```

- starts at `Integer.MAX_VALUE`
- traverses `values`, unboxing each
- replaces `smallest` when a value is smaller