

3. Users of a website are asked to provide a review of the website at the end of each visit. Each review, represented by an object of the `Review` class, consists of an integer indicating the user's rating of the website and an optional `String` comment field. The comment field in a `Review` object ends with a period ("."), exclamation point ("!"), or letter, or is a `String` of length 0 if the user did not enter a comment.

```
public class Review
{
    private int rating;
    private String comment;

    /** Precondition: r >= 0
     *     c is not null.
     */
    public Review(int r, String c)
    {
        rating = r;
        comment = c;
    }

    public int getRating()
    {
        return rating;
    }

    public String getComment()
    {
        return comment;
    }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

GO ON TO THE NEXT PAGE.

The `ReviewAnalysis` class contains methods used to analyze the reviews provided by users. You will write two methods of the `ReviewAnalysis` class.

```
public class ReviewAnalysis
{
    /** All user reviews to be included in this analysis */
    private Review[] allReviews;

    /** Initializes allReviews to contain all the Review objects to be analyzed */
    public ReviewAnalysis()
    { /* implementation not shown */ }

    /** Returns a double representing the average rating of all the Review objects to be
     * analyzed, as described in part (a)
     * Precondition: allReviews contains at least one Review.
     * No element of allReviews is null.
     */
    public double getAverageRating()
    { /* to be implemented in part (a) */ }

    /** Returns an ArrayList of String objects containing formatted versions of
     * selected user comments, as described in part (b)
     * Precondition: allReviews contains at least one Review.
     * No element of allReviews is null.
     * Postcondition: allReviews is unchanged.
     */
    public ArrayList<String> collectComments()
    { /* to be implemented in part (b) */ }
}
```

GO ON TO THE NEXT PAGE.

- (a) Write the `ReviewAnalysis` method `getAverageRating`, which returns the average rating (arithmetic mean) of all elements of `allReviews`. For example, `getAverageRating` would return 3.4 if `allReviews` contained the following `Review` objects.

0	1	2	3	4
4 "Good! Thx"	3 "OK site"	5 "Great!"	2 "Poor! Bad."	3 ""

Complete method `getAverageRating`.

```
/** Returns a double representing the average rating of all the Review objects to be
 * analyzed, as described in part (a)
 * Precondition: allReviews contains at least one Review.
 * No element of allReviews is null.
 */
public double getAverageRating()
```

Begin your response at the top of a new page in the Free Response booklet and fill in the appropriate circle indicating the question number.
If there are multiple parts to this question, write the part letter with your response.

Class information for this question

```
public class Review
private int rating
private String comment

public Review(int r, String c)
public int getRating()
public String getComment()

public class ReviewAnalysis
private Review[] allReviews

public ReviewAnalysis()
public double getAverageRating()
public ArrayList<String> collectComments()
```

GO ON TO THE NEXT PAGE.

- (b) Write the `ReviewAnalysis` method `collectComments`, which collects and formats only comments that contain an exclamation point. The method returns an `ArrayList` of `String` objects containing copies of user comments from `allReviews` that contain an exclamation point, formatted as follows. An empty `ArrayList` is returned if no comment in `allReviews` contains an exclamation point.

- The `String` inserted into the `ArrayList` to be returned begins with the index of the `Review` in `allReviews`.
- The index is immediately followed by a hyphen (" - ").
- The hyphen is followed by a copy of the original comment.
- The `String` must end with either a period or an exclamation point. If the original comment from `allReviews` does not end in either a period or an exclamation point, a period is added.

The following example of `allReviews` is repeated from part (a).

0	1	2	3	4
4 "Good! Thx"	3 "OK site"	5 "Great!"	2 "Poor! Bad."	3 ""

The following `ArrayList` would be returned by a call to `collectComments` with the given contents of `allReviews`. The reviews at index 1 and index 4 in `allReviews` are not included in the `ArrayList` to return since neither review contains an exclamation point.

"0-Good! Thx."	"2-Great!"	"3-Poor! Bad."
----------------	------------	----------------

Complete method `collectComments`.

```
/** Returns an ArrayList of String objects containing formatted versions of
 * selected user comments, as described in part (b)
 * Precondition: allReviews contains at least one Review.
 * No element of allReviews is null.
 * Postcondition: allReviews is unchanged.
 */
public ArrayList<String> collectComments()
```

Begin your response at the top of a new page in the Free Response booklet and fill in the appropriate circle indicating the question number.
If there are multiple parts to this question, write the part letter with your response.

GO ON TO THE NEXT PAGE.

3. A high school club maintains information about its members in a `MemberInfo` object. A `MemberInfo` object stores a club member's name, year of graduation, and whether or not the club member is in *good standing*. A member who is in good standing has fulfilled all the responsibilities of club membership.

A partial declaration of the `MemberInfo` class is shown below.

```
public class MemberInfo
{
    /** Constructs a MemberInfo object for the club member with name name,
     * graduation year gradYear, and standing hasGoodStanding.
     */
    public MemberInfo(String name, int gradYear, boolean hasGoodStanding)
    { /* implementation not shown */ }

    /** Returns the graduation year of the club member. */
    public int getGradYear()
    { /* implementation not shown */ }

    /** Returns true if the member is in good standing and false otherwise. */
    public boolean inGoodStanding()
    { /* implementation not shown */ }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

The `ClubMembers` class maintains a list of current club members. The declaration of the `ClubMembers` class is shown below.

```
public class ClubMembers
{
    private ArrayList<MemberInfo> memberList;

    /** Adds new club members to memberList, as described in part (a).
     * Precondition: names is a non-empty array.
     */
    public void addMembers(String[] names, int gradYear)
    { /* to be implemented in part (a) */ }

    /** Removes members who have graduated and returns a list of members who have graduated
     * and are in good standing, as described in part (b).
     */
    public ArrayList<MemberInfo> removeMembers(int year)
    { /* to be implemented in part (b) */ }

    // There may be instance variables, constructors, and methods that are not shown.
}
```

- (a) Write the `ClubMembers` method `addMembers`, which takes two parameters. The first parameter is a `String` array containing the names of new club members to be added. The second parameter is the graduation year of all the new club members. The method adds the new members to the `memberList` instance variable. The names can be added in any order. All members added are initially in good standing and share the same graduation year, `gradYear`.

Complete the `addMembers` method.

```
/** Adds new club members to memberList, as described in part (a).
 * Precondition: names is a non-empty array.
 */
public void addMembers(String[] names, int gradYear)
```

Begin your response at the top of a new page in the separate Free Response booklet and fill in the appropriate circle at the top of each page to indicate the question number. If there are multiple parts to this question, write the part letter with your response.

(b) Write the `ClubMembers` method `removeMembers`, which takes the following actions.

- Returns a list of all students who have graduated and are in good standing. A member has graduated if the member's graduation year is less than or equal to the method's `year` parameter. If no members meet these criteria, an empty list is returned.
- Removes from `memberList` all members who have graduated, regardless of whether or not they are in good standing.

The following example illustrates the results of a call to `removeMembers`.

The `ArrayList` `memberList` before the method call `removeMembers(2018)`:

"SMITH, JANE"	"FOX, STEVE"	"XIN, MICHAEL"	"GARCIA, MARIA"
2019	2018	2017	2020
false	true	false	true

The `ArrayList` `memberList` after the method call `removeMembers(2018)`:

"SMITH, JANE"	"GARCIA, MARIA"
2019	2020
false	true

The `ArrayList` returned by the method call `removeMembers(2018)`:

"FOX, STEVE"
2018
true

Complete the `removeMembers` method.

```
/** Removes members who have graduated and returns a list of members who have graduated and are
 * in good standing, as described in part (b).
 */
public ArrayList<MemberInfo> removeMembers(int year)
```

Begin your response at the top of a new page in the separate Free Response booklet and fill in the appropriate circle at the top of each page to indicate the question number. If there are multiple parts to this question, write the part letter with your response.

Class information for this question

```
public class MemberInfo
```

```
public MemberInfo(String name, int gradYear, boolean hasGoodStanding)
public int getGradYear()
public boolean inGoodStanding()
```

```
public class ClubMembers
```

```
private ArrayList<MemberInfo> memberList
```

```
public void addMembers(String[] names, int gradYear)
public ArrayList<MemberInfo> removeMembers(int year)
```

**COMPUTER SCIENCE A
SECTION II****Time—1 hour and 45 minutes****Number of questions—4****Percent of total score—50**

Directions: SHOW ALL YOUR WORK. REMEMBER THAT PROGRAM SEGMENTS ARE TO BE WRITTEN IN JAVA.

Notes:

- Assume that the classes listed in the Java Quick Reference have been imported where appropriate.
 - Unless otherwise noted in the question, assume that parameters in method calls are not `null` and that methods are called only when their preconditions are satisfied.
 - In writing solutions for each question, you may use any of the accessible methods that are listed in classes defined in that question. Writing significant amounts of code that can be replaced by a call to one of these methods will not receive full credit.
1. This question involves reasoning about one-dimensional and two-dimensional arrays of integers. You will write three static methods, all of which are in a single enclosing class, named `DiverseArray` (not shown). The first method returns the sum of the values of a one-dimensional array; the second method returns an array that represents the sums of the rows of a two-dimensional array; and the third method analyzes row sums.
- (a) Write a `static` method `arraySum` that calculates and returns the sum of the entries in a specified one-dimensional array. The following example shows an array `arr1` and the value returned by a call to `arraySum`.

<u>arr1</u>					Value returned by <u>arraySum(arr1)</u>
0	1	2	3	4	
1	3	2	7	3	16

WRITE YOUR SOLUTION ON THE NEXT PAGE.

Complete method `arraySum` below.

```
/** Returns the sum of the entries in the one-dimensional array arr.
 */
public static int arraySum(int[] arr)
```

Part (b) begins on page 4.

- (b) Write a `static` method `rowSums` that calculates the sums of each of the rows in a given two-dimensional array and returns these sums in a one-dimensional array. The method has one parameter, a two-dimensional array `arr2D` of `int` values. The array is in row-major order: `arr2D[r][c]` is the entry at row `r` and column `c`. The method returns a one-dimensional array with one entry for each row of `arr2D` such that each entry is the sum of the corresponding row in `arr2D`. As a reminder, each row of a two-dimensional array is a one-dimensional array.

For example, if `mat1` is the array represented by the following table, the call `rowSums(mat1)` returns the array `{16, 32, 28, 20}`.

	<u>mat1</u>				
	0	1	2	3	4
0	1	3	2	7	3
1	10	10	4	6	2
2	5	3	5	9	6
3	7	6	4	2	1

Methods written in this question

```
public static int arraySum(int[] arr)
public static int[] rowSums(int[][] arr2D)
public static boolean isDiverse(int[][] arr2D)
```

WRITE YOUR SOLUTION ON THE NEXT PAGE.

Assume that `arraySum` works as specified, regardless of what you wrote in part (a). You must use `arraySum` appropriately to receive full credit.

Complete method `rowSums` below.

```
/** Returns a one-dimensional array in which the entry at index k is the sum of
 * the entries of row k of the two-dimensional array arr2D.
 */
public static int[] rowSums(int[][] arr2D)
```

Part (c) begins on page 6.

- (c) A two-dimensional array is *diverse* if no two of its rows have entries that sum to the same value. In the following examples, the array `mat1` is diverse because each row sum is different, but the array `mat2` is not diverse because the first and last rows have the same sum.

<u>mat1</u>						
	0	1	2	3	4	Row sums
0	1	3	2	7	3	16
1	10	10	4	6	2	32
2	5	3	5	9	6	28
3	7	6	4	2	1	20

<u>mat2</u>						
	0	1	2	3	4	Row sums
0	1	1	5	3	4	14
1	12	7	6	1	9	35
2	8	11	10	2	5	36
3	3	2	3	0	6	14

Write a static method `isDiverse` that determines whether or not a given two-dimensional array is diverse. The method has one parameter: a two-dimensional array `arr2D` of `int` values. The method should return `true` if all the row sums in the given array are unique; otherwise, it should return `false`. In the arrays shown above, the call `isDiverse(mat1)` returns `true` and the call `isDiverse(mat2)` returns `false`.

Methods written in this question

```
public static int arraySum(int[] arr)
public static int[] rowSums(int[][] arr2D)
public static boolean isDiverse(int[][] arr2D)
```

Assume that `arraySum` and `rowSums` work as specified, regardless of what you wrote in parts (a) and (b). You must use `rowSums` appropriately to receive full credit.

Complete method `isDiverse` below.

```
/** Returns true if all rows in arr2D have different row sums;
 *     false otherwise.
 */
public static boolean isDiverse(int[][] arr2D)
```