4. Data Collections

Starter Quiz · 课前小测

AP Computer Science A Name: _____ Score: _____

1. A program that runs correctly is...
   - ☐ not automatically ethical
   - ☐ always ethical
   - ☐ always private
   - ☐ never biased
2. A structure that stores many values of the same type under one name is a(n)...
   - ☐ array
   - ☐ int
   - ☐ boolean
   - ☐ constructor
3. For int[] a = {10, 20, 30}; what is a[0]?
   - ☐ 10
   - ☐ 20
   - ☐ 30
   - ☐ there is no a[0]
4. The correct condition to traverse an array a with an index is...
   - ☐ i < a.length
   - ☐ i <= a.length
   - ☐ i < a.length()
   - ☐ i > 0
5. To find the maximum of an array, you should initialize max to...
   - ☐ the first element a[0]
   - ☐ 0
   - ☐ the array length
   - ☐ -1
6. For a = {3, 9, 5}, what is the maximum value?

   _____

7. A forward for loop with i++ and remove(i) skips the element after each removal.

   ☐ True ☐ False
8. An algorithm trained on biased data can amplify that unfairness at scale.

   ☐ True ☐ False
9. For int[] a = {10, 20, 30}; what is a.length?

   _____
10. In for (int x : a) { x = 0; }, the array a is set to all zeros.

    ☐ True ☐ False

4. Data Collections

Answers · 答案

AP Computer Science A

1. **not automatically ethical**

   Correct code can still violate privacy or amplify bias.

2. **array**

   An array is a fixed-size, same-type collection.

3. **10**

   Arrays are indexed from 0, so a[0] is the first element, 10.

4. **i < a.length**

   Valid indices are 0..length-1, so i < a.length.

5. **the first element a[0]**

   Starting at 0 fails if all values are negative.

6. **9**

   9 is the largest element.

7. **True**

   The shifted neighbor takes index i but is never checked.

8. **True**

   Bias in data can produce unjust outcomes for many people.

9. **3**

   Three elements → length 3.

10. **False**

    x is a local copy; the array is unchanged.