

5.4 Asymmetric Cryptography

Name: _____ Class: _____ Date: _____ **Total: 46 marks**

KEY WORDS private key 私钥 • public key 公钥 • asymmetric encryption 非对称加密
• key pair 密钥对 • keyspace 密钥空间

Objective

Build the skills to answer exam questions on **asymmetric encryption** 非对称加密: choosing the right key, why **key length** 密钥长度 matters, and applying RSA and ECC.

You must be able to:

- explain why asymmetric encryption needs no prearranged shared secret
- decide, for any transfer, **whose** key and **which** key of the pair is used
- explain what happens when a private key is exposed
- calculate a **keyspace** 密钥空间 and the average number of guesses to break it
- state the cost of longer keys and why recommendations change over time
- name common asymmetric algorithms and the applications that use them

1 Worked examples

Study these first. Each one shows the method for a task used later.

■ The problem asymmetric encryption solves

With symmetric encryption, both parties need the **same** key - so the key itself has to be delivered securely before any secure communication can happen. Asymmetric encryption removes that: two people who have never met, and have arranged **no shared secret**, can communicate securely.

Each entity that will **receive** data first generates a **key pair** - two binary strings of equal length generated together. One is published; one is kept.

■ Whose key, and which one

This is the single most-tested decision in the topic, and the rule is short:

Encrypt with the receiver's PUBLIC key. Only the receiver's PRIVATE key can decrypt it.

So work in this order:

1. **Who is receiving?** Not who is sending.
2. **Take that person's PUBLIC key** to encrypt.

3. The receiver decrypts with **their own PRIVATE key**, which never leaves them.

Example. Amir sends a file to Bhavna. Amir uses **Bhavna's public key**. Bhavna decrypts with **Bhavna's private key**. Amir's own key pair is not involved at all in this direction - and for Bhavna to reply, she encrypts with **Amir's public key**.

The common wrong answer is to encrypt with the sender's private key. That does not protect anything: the matching public key is published, so anyone could read it.

■ The private key is the whole security

The private key must be **stored securely**. If it is exposed, shared, stolen, corrupted or compromised, the key pair is no longer secure and must be replaced - and every message ever encrypted to that public key is readable by whoever holds the private key.

■ Key length and keyspace

- An **n-bit** binary key has a keyspace of 2^n - the number of possible keys.
- Guessing randomly, an adversary finds the key on average after $2^n \div 2$, i.e. 2^{n-1} , guesses.

Example. A 16-bit key has $2^{16} = 65\,536$ possible keys, so on average $2^{15} = 32\,768$ guesses. Add one bit and both numbers **double** - which is why key length is quoted in bits and why a small increase is a large gain.

Two qualifications the exam checks:

- **Longer keys cost time** - encryption and decryption both take longer, so length is a trade-off, not a free win.
- **Recommendations change**, because processing power and efficiency keep improving, so software guesses keys faster each year. A length considered safe a decade ago may not be now.
- **Compare like with like.** A key-length comparison is only valid **within the same algorithm**. A 256-bit ECC key and a 256-bit RSA key do not offer comparable security, and saying "longer is stronger" across two different algorithms is wrong.

■ The algorithms

Common asymmetric algorithms: **RSA** and **elliptic curve cryptography (ECC)**. They are used in digital signatures, secure web traffic and key exchange. As with symmetric encryption, the operations can be run from the **command line**, from specialised software, or through web-based tools - and in a CLI a user can generate a key pair and encrypt or decrypt files as needed.

2 Practice

2.1 Explain the advantage asymmetric encryption has over symmetric encryption when two people have never communicated before. [2]

2.2 Priya wants to send a confidential file to Wen.

(a) Whose key is used to encrypt it, and which key of the pair? [2]

(b) Whose key decrypts it, and which key of the pair? [2]

(c) Explain why encrypting with Priya's private key would not keep the file confidential. [2]

2.3 State **three** events that would require a key pair to be replaced. [3]

2.4 Calculate the keyspace and the average number of guesses for each key.

(a) An 8-bit key. [2]

(b) A 20-bit key. [2]

2.5 Explain what happens to the keyspace when one bit is added to a key. [2]

2.6 State **one** disadvantage of using a longer key. [1]

2.7 Explain why key-length recommendations are revised over time. [2]

2.8 A student claims “a 256-bit ECC key is exactly as strong as a 256-bit RSA key, because both are 256 bits”. Explain why this reasoning is wrong. [2]

2.9 Name **two** common asymmetric algorithms and **two** applications that use them. [4]

3 Exam-style questions

3.1 To send data securely to a receiver, the sender encrypts with [1]

A	B
C	D

- A the sender's private key
- B the sender's public key
- C the receiver's private key
- D the receiver's public key

3.2 A 12-bit key has a keyspace of [1]

A	B
C	D

- A 12
- B 24
- C 144
- D 4096

3.3 On average, how many guesses are needed to find an n-bit key at random? [1]

A	B
C	D

- A $n \div 2$
- B 2^n
- C 2^{n-1}
- D $2^n - 1$

3.4 Which statement about key length is correct?

[1]

- ☐ A longer keys are faster to encrypt and decrypt
☐ B key-length comparisons are only valid within the same algorithm
☐ C a longer key always removes the need for secure key storage
☐ D key-length recommendations are fixed once published

3.5 A small law firm exchanges case files with three external barristers. Each barrister generates an RSA key pair. The firm's practice manager keeps a folder of every barrister's public key, and also keeps a backup copy of the firm's own private key on a shared network drive "in case the office computer fails". Files are currently encrypted with 1024-bit RSA, a length chosen when the system was installed in 2012.

(a) Describe the correct procedure for the firm to send a confidential case file to one named barrister, and for that barrister to reply.

[4]

(b) Explain the risk created by the backup copy of the firm's private key, and state what must happen if that drive is compromised.

[3]

(c) The firm's 1024-bit key length was considered adequate in 2012. Explain, referring to processing power, why it may not be adequate now.

[3]

(d) A consultant proposes moving to 256-bit ECC and argues this must be weaker because "1024 is bigger than 256". Evaluate this argument.

[3]

(e) The practice manager asks why the firm should not simply use one shared symmetric key with all three barristers instead. Give **two** reasons, and state one situation in which symmetric encryption would still be preferable.

[3]