

Exercise walk-through

6.1

Data types, strings, exceptions and trace tables

International Baccalaureate · IB Diploma · Computer Science · HL

You must be able to

- choose a suitable **data type** for a value, and **cast** between types
- use string indexing, slicing and methods, and state what they return
- tell a **syntax error** from a **runtime error** and a **logic error**
- handle invalid input with `try ... except`
- complete a **trace table** for code with a loop and selection

1

The method

Method — Key knowledge: types and strings

Type	Python	Example
integer	int	42
real	float	3.75
Boolean	bool	True
string	str	"Ada"

- `input()` always returns a string: `int(input())` casts it to an integer.
- `7 / 2` is 3.5; `7 // 2` is 3; `7 % 2` is 1.

Exercises 2.1·2.2

2.1 State the most suitable data type for: (i) the number of seats in a cinema; (ii) the price of a ticket, 8.50; (iii) whether a seat is booked; (iv) a booking reference such as "K7-204". [4]

2.2 Evaluate: (i) $17 // 5$; (ii) $17 \% 5$; (iii) $17 / 5$. [3]

Exercises 2.1-2.2

2.1 State the most suitable data type for: (i) the number of seats in a cinema; (ii) the price of a ticket, 8.50; (iii) whether a seat is booked; (iv) a booking reference such as "K7-204". [4]

2.1

- (i) **integer**
- (ii) **real** (float)
- (iii) **Boolean**
- (iv) **string**: it holds letters and a hyphen

2.2 Evaluate: (i) $17 \text{ // } 5$; (ii) $17 \% 5$; (iii) $17 / 5$. [3]

2.2

- (i) **3**
- (ii) **2**
- (iii) **3.4**

Exercises 2.3-2.4

2.3 `code = "IB2027CS"`. State: (i) `len(code)`; (ii) `code[2:6]`; (iii) `code.find("C")`;
(iv) `code[-1]`. [4]

2.4 Classify each error as syntax, runtime or logic. [3]

- (i) `print("Total:", total` with no closing bracket
- (ii) an average calculated as `total / 10` when there are 12 items
- (iii) `marks[5]` when `marks` has 5 items

Exercises 2.3-2.4

2.3 `code = "IB2027CS".` State: (i) `len(code)`; (ii) `code[2:6]`; (iii) `code.find("C")`; (iv) `code[-1]`. [4]

2.3

- (i) **8**
- (ii) indexes 2 to 5: **"2027"**
- (iii) **6**
- (iv) the last character, **"S"**

2.4 Classify each error as syntax, runtime or logic. [3]

- (i) `print("Total:", total` with no closing bracket
- (ii) an average calculated as `total / 10` when there are 12 items
- (iii) `marks[5]` when `marks` has 5 items

2.4

- (i) **syntax**
- (ii) **logic**: it runs but gives the wrong answer
- (iii) **runtime**: an index error, as valid indexes are 0 to 4

Exercises 3.1-3.2

3.1 What is printed by `print("3" + "4")`?

[1]

☐

A 7

B 34

C "3" + "4"

D an error message

3.2 `word = "python"`. Which expression gives `"tho"`?

[1]

☐

A `word[2:4]`

B `word[2:5]`

C `word[3:5]`

D `word[3:6]`

Exercises 3.1-3.2

3.1 What is printed by `print("3" + "4")`?

[1]

☐

A 7

B 34

C "3" + "4"

D an error message

3.1 B

- + joins two strings

3.2 `word = "python"`. Which expression gives "tho"?

[1]

☐

A `word[2:4]`

B `word[2:5]`

C `word[3:5]`

D `word[3:6]`

3.2 B

- indexes 2, 3, 4: t, h, o

Exercise 3.3

3.3 Which input makes `int(input())` raise a `ValueError`?

[1]

☐

A 42

B -7

C 007

D 4.5

Exercise 3.3

3.3 Which input makes `int(input())` raise a `ValueError`?

[1]

☐

A 42

B -7

C 007

D 4.5

3.3 D

- `int` cannot convert text with a decimal point

Setup for exercise 3.4

3.4 A program reads temperatures until the user enters x.

```
count = 0
total = 0
high = -100
t = input()
while t != "x":
    v = int(t)
    count = count + 1
    total = total + v
    if v > high:
        high = v
    t = input()
print(total / count, high)
```

Exercise 3.4 (a)

(a) Complete a trace table for the inputs 18, 23, 19, x, with columns **t**, **count**, **total** and **high**, and state the output. [4]

Exercise 3.4 (a)

(a) Complete a trace table for the inputs 18, 23, 19, x, with columns `t`, `count`, `total` and `high`, and state the output. [4]

(a)

<code>t</code>	<code>count</code>	<code>total</code>	<code>high</code>
"18"	0	0	-100
	1	18	18
"23"	2	41	23
"19"	3	60	23
"x"			

- `count` and `total` correct
- `high` correct
- loop ends at x
- output **20.0 23**

Exercise 3.4 (b)

(b) State the output if the first input is $\mathbf{x}$, and explain why.

[2]

Exercise 3.4 (b)

(b) State the output if the first input is `x`, and explain why.

[2]

(b)

- the loop body never runs, so `count` is 0
- `total / count` divides by zero: a **ZeroDivisionError**, and nothing is printed

Exercise 3.4 (c)

(c) Explain why the program crashes if the user types `twenty`, and describe how `try ... except` would prevent it. [3]

Exercise 3.4 (c)

(c) Explain why the program crashes if the user types `twenty`, and describe how `try ... except` would prevent it. [3]

(c)

- `int("twenty")` raises a `ValueError`
- put the cast inside `try`
- the `except ValueError` block prints a message and asks again instead of stopping

Exercise 3.4 (d)

(d) Give **three** test inputs for the temperature, one normal, one boundary and one invalid, for a sensor that reads from -40 to 50. [3]

Exercise 3.4 (d)

(d) Give **three** test inputs for the temperature, one normal, one boundary and one invalid, for a sensor that reads from -40 to 50. [3]

(d)

- normal: e.g. 21
- boundary: -40 or 50
- invalid: e.g. 51, -41 or "abc"