

5.1 Algorithms, traces and correctness evidence

Name: _____ Class: _____ Date: _____ **Total: 10 marks**

KEY WORDS algorithm • boundary test

Objective

Algorithms, traces and correctness evidence. Supported SL concept preparation; original classroom practice, not an official IB paper or assessed learner work.


1 Key knowledge and worked examples

■ What would explain this observation?

- An **algorithm** can work for one example and fail at a boundary. Testing should be designed from the specification, not only the happy path.
- Start with a prediction. State the quantities or features you would compare, then decide what evidence could distinguish two explanations.

■ Build the model

- An algorithm is a finite, unambiguous procedure for a task. A trace records state changes. A loop invariant describes a property preserved by each iteration and helps justify correctness.
- algorithm: A finite procedure solving a stated task; **boundary test** : A test at a limit of the allowed input range.



■ Choose evidence that can test it

- State input conditions and expected outputs. Use boundary cases, empty collections where allowed, duplicates and invalid values. Distinguish a wrong algorithm from a wrong implementation or an incomplete requirement.
- Trace a search over a small fictional sorted list. State the indexing convention. For binary search, update bounds so the remaining interval shrinks and reject unsorted input unless sorting is part of the task.

■ Work from known quantities

- State the known values and their units. Choose the relation because its assumptions fit this case, then rearrange before substitution.
- Known: a linear search of an eight-item list can require eight comparisons when the sought item is last or absent. Doubling the list length doubles the worst-case comparison count under this model. Binary search reduces the interval by roughly half each step but requires a suitable ordered structure.

Example:

A linear search scans all 14 items without a match. How many item comparisons occur? Use the same sequence: known quantities → model → relation → substitution → unit and interpretation.

■ Check the conclusion and its limits

- A successful sample test does not prove correctness for all valid inputs. Do not import Cambridge-specific pseudocode syntax into an IB course without a course source.
- Return to the original observation. Explain what the result supports, which conditions it assumes, and one way to test a competing explanation.

Warn:

One successful sample test proves an algorithm correct for every valid input. This claim is false: A successful sample test does not prove correctness for all valid inputs. Do not import Cambridge-specific pseudocode syntax into an IB course without a course source.

Key:

Algorithms, traces and correctness evidence: State input conditions and expected outputs. Use boundary cases, empty collections where allowed, duplicates and invalid values. Distinguish a wrong algorithm from a wrong implementation or an incomplete requirement.

■ Runnable trace and boundary

```
def first_index(values, target):
    for index, value in enumerate(values):
        if value == target:
            return index
    return -1
print(first_index([4, 7, 4], 4))
print(first_index([4, 7, 4], 9))
print(first_index([], 4))
```

Expected output:

```
0
-1
-1
```

The loop tests index 0 first, stops on a match, and returns -1 only after exhausting the list. Duplicates therefore return the first index. An empty list executes no loop body.

2 Practice

2.1 What must hold before applying ordinary binary search to a list? Choose one answer.

- **A** The list is ordered under the comparison rule
- **B** Every value is different
- **C** The list contains exactly ten items

[1]

2.2 A linear search scans all 14 items without a match. How many item comparisons occur? Show the relation, substitution and units.

[2]

2.3 Decide whether this claim is true and justify: One successful sample test proves an algorithm correct for every valid input.

[2]

2.4 A finite procedure solving a stated task: write the technical term.

[1]

3 Exam-style questions

3.1 Trace first-match linear search on $[4,7,4]$ for 4 and 9. Give results and comparison counts, including an empty-list boundary. [4]

Solutions

2.1 A State input conditions and expected outputs. Use boundary cases, empty collections where allowed, duplicates and invalid values. Distinguish a wrong algorithm from a wrong implementation or an incomplete requirement.

2.2 One equality test per visited item; all 14 visited means 14 comparisons.

2.3 False. A successful sample test does not prove correctness for all valid inputs. Do not import Cambridge-specific pseudocode syntax into an IB course without a course source.

2.4 algorithm. algorithm means A finite procedure solving a stated task.

3.1 For 4 return index 0 after one comparison; for 9 return -1 after three. Empty list returns -1 after zero. Use zero-based indices and stop at the first match.