

Java Handout

English edition

Contents


1 Java basics

1.1 Classes, main & output

Every Java program lives inside a class . It starts at a method named `main`. `System.out.println(...)` prints a line; `System.out.print(...)` prints with no new line.

```
public class Main {  
    public static void main(String[] args) {  
        System.out.println("Hello, world!");  
        System.out.println("I am learning Java.");  
    }  
}
```

- Java is compiled : the compiler checks the whole program, then it runs.
- Every statement ends with a semicolon ;.



Exam tip: every program lives in a class; execution starts at `main`; end each statement with ;

Java programs live in a class and start at main

1.2 Variables & primitive types

A variable must declare its type. Common primitive types : `int` (whole number), `double` (decimal), `boolean` (true/false), `char` (one letter).

```
public class Main {
    public static void main(String[] args) {
        int age = 17;
        double price = 9.99;
        boolean passed = true;
        System.out.println(age + " " + price + " " + passed);
    }
}
```

1.3 Comments & style

A comment is `//` (one line) or `/* ... */` (a block). Indent the code inside braces `{ }`. Class names start Capitalised; variables and methods use camelCase (lowercase first).

```
public class Main {
    public static void main(String[] args) {
        // greet the user
        String firstName = "Mei";
        System.out.println("Hi, " + firstName);
    }
}
```

Common mistakes

- Every statement ends with a semicolon `;`.
- `main` must be exactly `public static void main(String[] args)`.
- `println` adds a new line; `print` does not.

2 Operators & expressions

2.1 Arithmetic & assignment

Java arithmetic uses + - * / and % (remainder). With two `ints`, / is integer division — it drops the decimal. +=, -=, and ++ are shortcuts.

```
public class Main {  
    public static void main(String[] args) {  
        int a = 7, b = 2;  
        System.out.println(a / b);    // 3 (integer division)  
        System.out.println(a % b);    // 1  
        double x = 7.0 / 2;           // 3.5 (one side is double)  
        System.out.println(x);  
    }  
}
```

integer division

7 / 2 → 3
(int / int)

floating division

7.0 / 2 → 3.5
(double involved)

Exam tip: int/int drops the decimal; make one side double for a real quotient; % is remainder

int/int truncates; involve a double for a real quotient

2.2 Using objects: String, Math, wrappers

Some values are objects with methods. `String` has `.length()`, `.substring()`, `.toUpperCase()`. `Math` has `Math.max`, `Math.sqrt`, `Math.pow`. Wrapper classes (`Integer`, `Double`) wrap a primitive — e.g. `Integer.parseInt("42")`.

```
public class Main {
    public static void main(String[] args) {
        String s = "Hello";
        System.out.println(s.length());           // 5
        System.out.println(s.toUpperCase());       // HELLO
        System.out.println(Math.max(3, 9));        // 9
        System.out.println(Integer.parseInt("42") + 1); // 43
    }
}
```

`Math.random()` returns a random double from 0.0 up to (but not including) 1.0. Scale it and cast to get whole numbers — this is the AP idiom:

```
public class Main {
    public static void main(String[] args) {
        // a random whole number from 1 to 6 (a dice roll)
        int roll = (int) (Math.random() * 6) + 1;
        System.out.println(roll >= 1 && roll <= 6); // true
    }
}
```

- `Integer.MAX_VALUE` (2147483647) and `Integer.MIN_VALUE` are the limits of `int`; going past them wraps around (an overflow).
- An object variable that points at no object holds `null`; calling a method on it throws a `NullPointerException`.

2.3 Casting & type conversion

A cast changes a value's type. `(int)` drops the decimal; `(double)` avoids integer division when you need an exact result.

```
public class Main {  
    public static void main(String[] args) {  
        double pi = 3.99;  
        System.out.println((int) pi);           // 3  
        int total = 7, n = 2;  
        System.out.println((double) total / n); // 3.5  
    }  
}
```

Common mistakes


- Integer division: `5 / 2` is 2, not 2.5. Cast first: `(double) 5 / 2`.
- Compare Strings (and other objects) with `.equals()`, not `==`.
- `==` on two objects tests whether they are the SAME object, not whether they look equal.

3 Booleans & selection

3.1 if / else

`if` runs a block when a condition is true; `else if` and `else` add more cases. The condition goes in (), the block in { }.

```
public class Main {  
    public static void main(String[] args) {  
        int score = 72;  
        if (score >= 80) {  
            System.out.println("A");  
        } else if (score >= 60) {  
            System.out.println("B");  
        } else {  
            System.out.println("fail");  
        }  
    }  
}
```



Exam tip: always use braces; else if chains more cases; only one branch runs

if chooses the true branch; else the false branch

3.2 Logical operators & comparisons

Compare with `==`, `!=`, `<`, `>`, `<=`, `>=` — a comparison gives a `boolean`. Combine with `&&` (and), `||` (or), `!` (not) — the logical operators. For `Strings`, use `.equals(...)`, `not ==`.

```
public class Main {
    public static void main(String[] args) {
        int age = 16;
        boolean member = true;
        System.out.println(age >= 18 && member);    // false
        String a = "hi";
        System.out.println(a.equals("hi"));        // true
    }
}
```

3.3 switch

`switch` chooses among many fixed values. Each `case` ends with `break`; default is the fallback.

```
public class Main {
    public static void main(String[] args) {
        int day = 3;
        switch (day) {
            case 1: System.out.println("Mon"); break;
            case 3: System.out.println("Wed"); break;
            default: System.out.println("other");
        }
    }
}
```

Common mistakes


- A condition must be a `boolean`; `if (x = 5)` does not compile (use `==`).
- Each `switch` case needs a `break`; or control falls through to the next case.
- `&&` and `||` are the logical operators; `&` and `|` are bitwise.

4 Loops

4.1 while loops

A **while** loop repeats while a condition is true. Change something inside, or it loops forever.

```
public class Main {  
    public static void main(String[] args) {  
        int n = 1;  
        while (n <= 3) {  
            System.out.println(n);  
            n++;  
        }  
    }  
}
```



Exam tip: condition is checked before each pass; body must eventually make it false

while checks the condition before each pass of the body

4.2 for loops

A for loop packs the start, the condition, and the step into one line. Best when you know the count.

```
public class Main {
    public static void main(String[] args) {
        for (int i = 0; i < 5; i++) {
            System.out.print(i + " ");
        }
        System.out.println();    // 0 1 2 3 4
    }
}
```

4.3 Accumulation

The accumulator pattern: start a variable before the loop, then update it each turn.

```
public class Main {
    public static void main(String[] args) {
        int total = 0;
        for (int i = 1; i <= 5; i++) {
            total += i;
        }
        System.out.println(total);    // 15
    }
}
```

4.4 Nested loops

A loop inside a loop is a nested loop . The inner loop runs fully on each turn of the outer one.

```
public class Main {
    public static void main(String[] args) {
        for (int r = 0; r < 3; r++) {
            for (int c = 0; c < 3; c++) {
                System.out.print("*");
            }
            System.out.println();
        }
    }
}
```

Common mistakes

- `for (int i = 0; i < n; i++)` runs `n` times (0 to `n - 1`); using `<=` runs one extra.
- Do not put a semicolon right after `for (...)` or `while (...)` — it makes an empty loop.
- Declare the counter in the `for` header so its scope ends with the loop.

5 Strings

5.1 String methods

A `String` is text. Useful methods: `.length()`, `.charAt(i)`, `.substring(a, b)`, `.indexOf(x)`, `.toUpperCase()`, `.equals(...)`. Strings are immutable — each method returns a **new** `String`.

```
public class Main {
    public static void main(String[] args) {
        String s = "Python";
        System.out.println(s.length());           // 6
        System.out.println(s.charAt(0));          // P
        System.out.println(s.substring(0, 3));    // Pyt
        System.out.println(s.toUpperCase());      // PYTHON
    }
}
```

The methods you will use every day:

Method	Meaning	Example → result
<code>.length()</code>	how many characters	<code>"Hi".length()</code> → 2
<code>.charAt(i)</code>	one character	<code>"Hi".charAt(0)</code> → H
<code>.substring(a, b)</code>	part, stops before b	<code>"Python".substring(0, 3)</code> → Pyt
<code>.substring(a)</code>	from a to the end	<code>"Python".substring(3)</code> → hon
<code>.indexOf(x)</code>	first position, -1 if absent	<code>"banana".indexOf("na")</code> → 2
<code>.equals(s)</code>	same text?	<code>"hi".equals("hi")</code> → true
<code>.compareTo(s)</code>	order: negative / 0 / positive	<code>"apple".compareTo("banana")</code> → negative

`compareTo` puts Strings in dictionary order — the AP exam uses it for sorting questions:

```
public class Main {
    public static void main(String[] args) {
        String a = "apple", b = "banana";
        System.out.println(a.compareTo(b) < 0);    // true (apple comes
↪ first)
        System.out.println(a.compareTo("apple")); // 0 (equal)
    }
}
```

length() how many chars	charAt(i) char at index i	substring slice a part	equals same text? (not ==)
--------------------------------------	--	-------------------------------------	---

Exam tip: Strings are objects — use equals for text, not ==; indices start at 0

Key String methods: length, charAt, substring, equals

5.2 Building & traversing strings

Join strings with + (concatenation). Visit each character with a loop and `.charAt(i)`.

```
public class Main {
    public static void main(String[] args) {
        String word = "banana";
        int count = 0;
        for (int i = 0; i < word.length(); i++) {
            if (word.charAt(i) == 'a') count++;
        }
        System.out.println(count);    // 3
    }
}
```

When you build a long String in a loop, `StringBuilder` is much faster: append the pieces, then call `.toString()` once.

```
public class Main {
    public static void main(String[] args) {
        StringBuilder sb = new StringBuilder();
        for (int i = 1; i <= 5; i++) {
            sb.append(i).append(" ");
        }
        System.out.println(sb.toString().trim());    // 1 2 3 4 5
    }
}
```

Common mistakes

- Strings are immutable: `s.toUpperCase()` returns a new String, so store the result.

- Read a character with `s.charAt(i)`; the length is `s.length()` (a method, with `()`).
- Building a `String` with `+=` in a big loop is slow; use a `StringBuilder`.

6 Arrays

6.1 1-D arrays

An array holds a fixed number of values of one type. Index from 0, and get the size with `.length`.

```
public class Main {  
    public static void main(String[] args) {  
        int[] scores = {88, 71, 95};  
        System.out.println(scores[0]);    // 88  
        System.out.println(scores.length); // 3  
        scores[1] = 100;  
        System.out.println(scores[1]);    // 100  
    }  
}
```


`int n = 7;`



n

a primitive holds
its value directly

`int[] a = {88, 71, 95};`



a (a reference)



[0]

[1]

[2]

a.length
= 3

the array object

06-array-memory

A primitive holds its value; an array variable holds a reference to the array object

6.2 Array algorithms

Walk the array with a loop to find a max, a total, a count, or to search . A for-each loop (`for (int x : a)`) reads each value in turn.

```
public class Main {
    public static void main(String[] args) {
        int[] a = {3, 9, 2, 7};
        int max = a[0], total = 0;
        for (int x : a) {
            if (x > max) max = x;
            total += x;
        }
        System.out.println(max + " " + total);    // 9 21
    }
}
```

6.3 2-D arrays

A 2-D array is a grid of rows and columns: `grid[row][col]`.

```
public class Main {
    public static void main(String[] args) {
        int[][] grid = {{1, 2, 3}, {4, 5, 6}};
        System.out.println(grid[1][2]);    // 6
        for (int[] row : grid) {
            for (int v : row) System.out.print(v + " ");
        }
        System.out.println();              // 1 2 3 4 5 6
    }
}
```

Common mistakes

- An array's size is `a.length` (no brackets, no `()`), and it is fixed when created.
- Valid indexes are 0 to `a.length - 1`; `a[a.length]` throws `ArrayIndexOutOfBoundsException`.
- A new `int[5]` is filled with zeros, not left empty.

7 ArrayList

7.1 ArrayList basics

An `ArrayList` is a resizable list — it grows and shrinks as you add or remove items. It stores objects, so use a wrapper type like `Integer` (not `int`). The `<Integer>` part is a generic type. Key methods: `.add(x)`, `.get(i)`, `.set(i, x)`, `.size()`, `.remove(i)`.

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<Integer> nums = new ArrayList<Integer>();
        nums.add(10);
        nums.add(20);
        nums.add(30);
        System.out.println(nums.size());    // 3
        System.out.println(nums.get(1));    // 20
        nums.set(0, 99);
        System.out.println(nums);           // [99, 20, 30]
    }
}
```

ArrayList grows as you add



Exam tip: `ArrayList<Type>` needs a type; indices start at 0 like arrays

ArrayList: add, get, size on a resizable list

7.2 ArrayList algorithms & the remove bug

`.remove(i)` shifts every later element one place left. If you remove while counting **i up**, you skip the next element. Fix: loop **backwards**, or don't increment **i** after a remove.

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<Integer> nums = new ArrayList<Integer>();
        for (int n : new int[]{4, 7, 4, 9, 4}) nums.add(n);
        // Remove every 4 - loop backwards so removals don't skip items.
        for (int i = nums.size() - 1; i >= 0; i--) {
            if (nums.get(i) == 4) nums.remove(i);
        }
        System.out.println(nums);    // [7, 9]
    }
}
```

Common mistakes

- `ArrayList` uses `.size()`, `.get(i)` and `.add(...)` — not the `[]` you use on arrays.
- Removing items while looping forward by index skips the next item (the remove bug). Loop backwards, or use an iterator.
- Store objects, not primitives: use `ArrayList<Integer>`, and Java auto-boxes `int` values.

8 Writing classes

8.1 Fields, constructor & methods

A class is a blueprint for objects. Its fields store data, its constructor sets up a new object, and its methods are the actions. `this.name` means "this object's name". Create an object with `new`.

```
public class Main {
    public static void main(String[] args) {
        Dog d = new Dog("Rex", 3);
        System.out.println(d.describe());    // Rex is 3 years old
        d.haveBirthday();
        System.out.println(d.describe());    // Rex is 4 years old
    }
}

class Dog {
    private String name;
    private int age;

    public Dog(String name, int age) {    // constructor
        this.name = name;
        this.age = age;
    }

    public String describe() {
        return name + " is " + age + " years old";
    }

    public void haveBirthday() {
        age++;
    }
}
```


A **static** member belongs to the class itself, not to any one object. Call a static method on the class name — like `Math.max` — and a static field is shared by every object:

```
public class Main {
    public static void main(String[] args) {
        System.out.println(Counter.made());    // 0
        new Counter();
        new Counter();
        System.out.println(Counter.made());    // 2
    }
}

class Counter {
    private static int count = 0;           // shared by ALL Counter objects

    public Counter() { count++; }

    public static int made() {              // called on the class:
↪    Counter.made()
        return count;
    }
}
```



Exam tip: constructor name matches the class; fields store state; methods do work

Fields store state; constructor builds; methods act

8.2 Encapsulation

Encapsulation means hiding data behind methods. Mark fields `private` so outside code can't touch them directly; expose an accessor (getter) to read, and a method to change them safely. The method can **guard** the data — here a deposit must be positive.

```
public class Main {
    public static void main(String[] args) {
        Account a = new Account(100);
        a.deposit(50);
        a.deposit(-999);           // rejected by the guard
        System.out.println(a.getBalance()); // 150
    }
}

class Account {
    private int balance;           // hidden from outside

    public Account(int start) {
        balance = start;
    }

    public void deposit(int amount) {
        if (amount > 0) balance += amount; // guard keeps balance
        ↪ valid
    }

    public int getBalance() {       // accessor (getter)
        return balance;
    }
}
```

Common mistakes

- A constructor has the class name and no return type (not even `void`).
- Use `this.field` to tell a field apart from a parameter with the same name.
- Make fields `private` and reach them through getter/setter methods (encapsulation).

9 Inheritance & polymorphism


9.1 Inheritance

Inheritance lets a subclass reuse a superclass . Write class `Cat` extends `Animal` and `Cat` gets `Animal`'s fields and methods for free. Call the parent constructor with `super(...)`.

```
public class Main {
    public static void main(String[] args) {
        Cat c = new Cat("Milo");
        c.eat();           // Milo is eating (inherited from Animal)
        c.speak();         // Meow (Cat's own method)
    }
}

class Animal {
    protected String name;
    public Animal(String name) { this.name = name; }
    public void eat() { System.out.println(name + " is eating"); }
}

class Cat extends Animal {
    public Cat(String name) { super(name); } // call Animal's
    ↪ constructor
    public void speak() { System.out.println("Meow"); }
}
```



Cat and Dog inherit name and eat(), and add their own speak()

09-inheritance

Cat and Dog extend Animal: they inherit its members and add their own

9.2 Polymorphism & toString

A subclass can override a method to replace the parent's version. Polymorphism means a `Shape` variable can hold any subtype, and Java picks the right `toString` at run time. `System.out.println(obj)` automatically calls `obj.toString()`.

```
public class Main {
    public static void main(String[] args) {
        Shape[] shapes = { new Circle(2), new Square(3) };
        for (Shape s : shapes) {
            System.out.println(s);           // each calls its own
            ↪ toString
        }
    }

    class Shape {
        public String toString() { return "a shape"; }
    }

    class Circle extends Shape {
        private int r;
        public Circle(int r) { this.r = r; }
        public String toString() { return "Circle r=" + r; } // override
    }

    class Square extends Shape {
        private int side;
        public Square(int side) { this.side = side; }
        public String toString() { return "Square side=" + side; } //
        ↪ override
    }
}
```


Common mistakes

- An overriding method must match the signature exactly; add `@Override` so the compiler catches slips.
- `super(...)` must be the first line of a subclass constructor.
- A subclass object IS-A superclass object, but not the other way round.

10 Recursion

10.1 Recursion

Recursion is a method that calls itself. Every recursion needs a base case (when to stop) and a recursive call that moves toward it. Without a base case it never stops and crashes with a *stack overflow*.



10-call-stack

The call stack for factorial(3): each call waits, then returns in reverse order

```
public class Main {
    public static void main(String[] args) {
        System.out.println(factorial(5)); // 120
    }

    public static int factorial(int n) {
        if (n <= 1) return 1;           // base case
        return n * factorial(n - 1);    // recursive call: n * (n-1)!
    }
}
```

Trace it: `factorial(5)` waits for `factorial(4)`, which waits for `factorial(3)`... down to `factorial(1)` returning 1. Then the answers multiply back up: $1 \rightarrow 2 \rightarrow 6 \rightarrow 24 \rightarrow 120$.

Recursion also works on Strings — peel off one character each call:

```
public class Main {  
    public static void main(String[] args) {  
        System.out.println(reverse("PYTHON"));    // NOHTYP  
    }  
  
    static String reverse(String s) {  
        if (s.length() <= 1) return s;            // base case  
        return reverse(s.substring(1)) + s.charAt(0);  
    }  
}
```

Merge sort is the recursive sort on the AP exam: split the array in half, sort each half recursively, then merge the two sorted halves. It runs in $O(n \log n)$ — far faster than the $O(n^2)$ sorts on big arrays.

```
import java.util.Arrays;

public class Main {
    public static void main(String[] args) {
        int[] a = {5, 2, 9, 1, 7, 3};
        mergeSort(a, 0, a.length - 1);
        System.out.println(Arrays.toString(a));    // [1, 2, 3, 5, 7, 9]
    }

    static void mergeSort(int[] a, int lo, int hi) {
        if (lo >= hi) return;                      // base case: one element
        int mid = (lo + hi) / 2;
        mergeSort(a, lo, mid);                      // sort the left half
        mergeSort(a, mid + 1, hi);                  // sort the right half
        merge(a, lo, mid, hi);                      // merge the two halves
    }

    static void merge(int[] a, int lo, int mid, int hi) {
        int[] tmp = new int[hi - lo + 1];
        int i = lo, j = mid + 1, k = 0;
        while (i <= mid && j <= hi) {
            if (a[i] <= a[j]) tmp[k++] = a[i++];
            else tmp[k++] = a[j++];
        }
        while (i <= mid) tmp[k++] = a[i++];
        while (j <= hi) tmp[k++] = a[j++];
        for (k = 0; k < tmp.length; k++) a[lo + k] = tmp[k];
    }
}
```

Common mistakes

- Recursion needs a base case, or it throws `StackOverflowError`.
- Each recursive call must move CLOSER to the base case.
- Trace a small example by hand to check the recursion returns the right value.
- In merge sort, the merge step does the real work; the recursion only splits the array.

11 Searching & sorting

11.1 Linear & binary search

Linear search checks every element — works on any array. Binary search is much faster but needs a **sorted** array: it looks at the middle, then throws away half each step. Both return the index, or -1 if not found.

```
public class Main {
    public static void main(String[] args) {
        int[] a = {2, 5, 8, 12, 16, 23};    // sorted, so binary search
        ↪ works
        System.out.println(linear(a, 12));    // 3
        System.out.println(binary(a, 12));    // 3
        System.out.println(binary(a, 9));    // -1 (not found)
    }

    static int linear(int[] a, int target) {
        for (int i = 0; i < a.length; i++)
            if (a[i] == target) return i;
        return -1;
    }

    static int binary(int[] a, int target) {
        int lo = 0, hi = a.length - 1;
        while (lo <= hi) {
            int mid = (lo + hi) / 2;
            if (a[mid] == target) return mid;
            else if (a[mid] < target) lo = mid + 1;
            else hi = mid - 1;
        }
        return -1;
    }
}
```

binary search for 16 (the array must be sorted)

step 1

2	5	8	12	16	23	38
---	---	---	----	----	----	----

 mid = 12 < 16 -> search the right half

step 2

2	5	8	12	16	23	38
---	---	---	----	----	----	----

 mid = 23 > 16 -> search the left half

step 3

2	5	8	12	16	23	38
---	---	---	----	----	----	----

 mid = 16 -> found at index 4

[0] [1] [2] [3] [4] [5] [6]

11-binary-search

Binary search halves the range each step, so a sorted array is searched in $O(\log n)$

11.2 Selection & insertion sort

Selection sort repeatedly finds the smallest remaining value and swaps it to the front. Insertion sort takes each value and slides it back into its place among the already-sorted values.

```
import java.util.Arrays;

public class Main {
    public static void main(String[] args) {
        int[] a = {5, 2, 9, 1, 7};
        for (int i = 0; i < a.length - 1; i++) {
            int min = i;
            for (int j = i + 1; j < a.length; j++)
                if (a[j] < a[min]) min = j;
            int t = a[min]; a[min] = a[i]; a[i] = t;    // swap into place
        }
        System.out.println(Arrays.toString(a));    // [1, 2, 5, 7, 9]
    }
}
```

```

import java.util.Arrays;

public class Main {
    public static void main(String[] args) {
        int[] a = {5, 2, 9, 1, 7};
        for (int i = 1; i < a.length; i++) {
            int key = a[i], j = i - 1;
            while (j >= 0 && a[j] > key) {    // shift bigger values
↪      right
                a[j + 1] = a[j];
                j--;
            }
            a[j + 1] = key;                  // drop key into the gap
        }
        System.out.println(Arrays.toString(a));    // [1, 2, 5, 7, 9]
    }
}

```

How the speeds compare:

Algorithm	Time
linear search	$O(n)$
binary search	$O(\log n)$, sorted arrays only
selection / insertion sort	$O(n^2)$
merge sort (topic 10)	$O(n \log n)$

Common mistakes

- Binary search only works on a **sorted** array.
- Linear search is $O(n)$; binary search is $O(\log n)$ but needs the sort first.
- Selection and insertion sort are $O(n^2)$ — clear to learn, slow on big data.

12 Files & the FRQ

12.1 Text files with Scanner

A `Scanner` reads text one line at a time. For a real file you write `new Scanner(new File("scores.txt"))`; here we wrap a `String` so the example runs anywhere. Use `.split(" ")` to split a line into parts and `Integer.parseInt(...)` to parse a number from text.

```
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        // Real file: Scanner in = new Scanner(new File("scores.txt"));
        String data = "Alice 80\nBob 95\nCara 72";
        Scanner in = new Scanner(data);
        int total = 0, count = 0;
        while (in.hasNextLine()) {
            String line = in.nextLine();
            String[] parts = line.split(" ");    // break the line on
            ↪ the space
            total += Integer.parseInt(parts[1]);
            count++;
        }
        System.out.println("average = " + (total / count)); // average
        ↪ = 82
    }
}
```

Read text line by line



Exam tip: `hasNextLine` guards the loop; `split` + `parseInt` turn a line into data

Scanner reads lines while `hasNextLine` is true

12.2 The AP FRQ question types

The AP CS A exam has four free-response questions, each a fixed shape:

- **Q1 — Methods & control:** write methods to a given spec; loops, `if`, `String/Math`.
- **Q2 — Class design:** write a full class (fields, constructor, methods) from a description.
- **Q3 — Array / ArrayList:** process a 1-D array or `ArrayList` (search, count, build a new list).
- **Q4 — 2-D array:** traverse a grid by row and column.

The skill is always the same: read the spec, write the method exactly as described, return the right type.

```
public class Main {
    public static void main(String[] args) {
        // Q1 style: implement a method to a spec, then it is tested.
        System.out.println(countEven(new int[]{4, 7, 10, 3, 6})); // 3
    }

    /** Returns how many values in arr are even. */
    public static int countEven(int[] arr) {
        int count = 0;
        for (int x : arr)
            if (x % 2 == 0) count++;
        return count;
    }
}
```

Common mistakes

- `nextInt()` leaves the newline behind, so a following `nextLine()` reads an empty line — read it away first.
- Check `hasNext()` before reading, to avoid running off the end of the file.
- In the FRQ, read the method header carefully: match the return type and parameters exactly.