

String operations

Ref Pseudocode

LENGTH, UCASE and LCASE

0478 publishes four string routines and no others. Three of them are here.

LENGTH(<identifier>) returns how many characters a string holds — spaces included.

```
OUTPUT LENGTH("Happy Days")
OUTPUT LENGTH("")
```

UCASE(<identifier>) returns the string in upper case , LCASE(<identifier>) in lower case . Neither changes the original — each hands back a new value.

```
DECLARE Name : STRING
Name ← "Happy"
OUTPUT UCASE(Name)
OUTPUT LCASE(Name)
OUTPUT Name
```

That last line still prints Happy: to keep the change you must assign it back.

```
DECLARE Name : STRING
Name ← "Happy"
Name ← UCASE(Name)
OUTPUT Name
```

Comparing without worrying about case

UCASE on both sides is the standard way to accept an answer however it was typed:

```
DECLARE Answer : STRING
Answer ← "yes"
IF UCASE(Answer) = "YES"
    THEN
        OUTPUT "Accepted"
ENDIF
```

Common mistakes

- Expecting UCASE(Name) to change Name. Assign the result back.

- LENGTH counts characters, not words. LENGTH("Happy Days") is 10.

SUBSTRING

SUBSTRING(<identifier>, <start>, <length>) pulls a piece out of a string — starting at position **start**, taking **length** characters.

```
OUTPUT SUBSTRING("Happy Days", 1, 5)
OUTPUT SUBSTRING("Happy Days", 7, 4)
```

△ **Counting starts at 1**, not 0. The first character of "Happy Days" is at position 1.

Taking one character, and the rest

```
DECLARE Word : STRING
Word ← "Computer"
OUTPUT "First letter: ", SUBSTRING(Word, 1, 1)
OUTPUT "Last letter: ", SUBSTRING(Word, LENGTH(Word), 1)
OUTPUT "Without the first: ", SUBSTRING(Word, 2, LENGTH(Word) - 1)
```

LENGTH inside SUBSTRING is what makes the last two lines work for a word of any size — hard-coding 8 would break the moment the word changed.

Reading a string one character at a time

```
DECLARE Word : STRING
DECLARE Index : INTEGER
Word ← "Cat"
FOR Index ← 1 TO LENGTH(Word)
    OUTPUT SUBSTRING(Word, Index, 1)
NEXT Index
```

Common mistakes

- Starting at 0. Position 1 is the first character.
- Reading the third argument as an *end position*. It is a **count** — SUBSTRING(W, 2, 3) takes three characters beginning at the second.
- Asking for more characters than the string has.