

# Cambridge Pseudocode Handout

English edition

## Contents

|           |                                           |           |
|-----------|-------------------------------------------|-----------|
| <b>1</b>  | <b>Style and layout</b>                   | <b>3</b>  |
| 1.1       | Keywords and case . . . . .               | 3         |
| 1.2       | Identifiers . . . . .                     | 3         |
| 1.3       | Comments and indentation . . . . .        | 4         |
| <b>2</b>  | <b>Variables, constants and types</b>     | <b>6</b>  |
| 2.1       | The five data types . . . . .             | 6         |
| 2.2       | DECLARE . . . . .                         | 7         |
| 2.3       | CONSTANT . . . . .                        | 7         |
| <b>3</b>  | <b>Assignment, input and output</b>       | <b>9</b>  |
| 3.1       | The assignment arrow . . . . .            | 9         |
| 3.2       | INPUT and OUTPUT . . . . .                | 10        |
| <b>4</b>  | <b>Arithmetic and logic</b>               | <b>11</b> |
| 4.1       | Arithmetic operators . . . . .            | 11        |
| 4.2       | DIV and MOD . . . . .                     | 11        |
| 4.3       | Relational and logic operators . . . . .  | 12        |
| <b>5</b>  | <b>String operations</b>                  | <b>14</b> |
| 5.1       | LENGTH, UCASE and LCASE . . . . .         | 14        |
| 5.2       | SUBSTRING . . . . .                       | 15        |
| <b>6</b>  | <b>Selection</b>                          | <b>16</b> |
| 6.1       | IF, THEN, ELSE, ENDIF . . . . .           | 16        |
| 6.2       | CASE OF . . . . .                         | 18        |
| <b>7</b>  | <b>Iteration</b>                          | <b>20</b> |
| 7.1       | FOR, the counted loop . . . . .           | 20        |
| 7.2       | WHILE, the pre-condition loop . . . . .   | 21        |
| 7.3       | REPEAT, the post-condition loop . . . . . | 22        |
| <b>8</b>  | <b>Arrays</b>                             | <b>24</b> |
| 8.1       | One-dimensional arrays . . . . .          | 24        |
| 8.2       | Two-dimensional arrays . . . . .          | 26        |
| <b>9</b>  | <b>Procedures and functions</b>           | <b>28</b> |
| 9.1       | PROCEDURE and CALL . . . . .              | 28        |
| 9.2       | FUNCTION and RETURN . . . . .             | 28        |
| 9.3       | Parameters . . . . .                      | 30        |
| <b>10</b> | <b>File handling</b>                      | <b>31</b> |

|                                            |           |
|--------------------------------------------|-----------|
| 10.1 Writing to a file . . . . .           | 31        |
| 10.2 Reading a file to the end . . . . .   | 32        |
| <b>11 A-Level 9618: what changes</b>       | <b>34</b> |
| 11.1 Layout and operators . . . . .        | 34        |
| 11.2 Parameters: BYVAL and BYREF . . . . . | 35        |
| 11.3 Records and other types . . . . .     | 36        |

# 1 Style and layout

## 1.1 ■ Keywords and case

Pseudocode is the language Cambridge writes algorithms in. It is not a real programming language – no computer runs it – but the exam marks it as if it were, so the form matters.

Every keyword is written in **upper case**: IF, REPEAT, PROCEDURE, OUTPUT.

```
DECLARE Count : INTEGER
Count ← 3
IF Count > 0
    THEN
        OUTPUT "Ready"
ENDIF
```

- Write IF, never if or If.
- A keyword can never be used as a name of your own: you may not call a variable FOR.

### Common mistakes

- Lower-case keywords. The mark scheme expects upper case.
- Inventing keywords. Only the words in this handout are in the syllabus.

## 1.2 ■ Identifiers

An **identifier** is the name you give a variable, a constant, a procedure or a function.

```
DECLARE NumberOfPlayers : INTEGER
NumberOfPlayers ← 4
OUTPUT NumberOfPlayers
```

Four rules, all from the syllabus:

- It must **start with a capital letter**: Count, not count.
- It may hold only letters and digits – no spaces, no punctuation.
- It is not **case-sensitive**, so Count and COUNT are the same name. Pick one spelling and keep it.
- Make it mean something. NumberOfPlayers earns the reader's time; N does not.

### Common mistakes

- count ← 0 – a lower-case start. 0478 requires the capital.
- Number of players – spaces are not allowed inside a name.

1.3 ■ Comments and indentation


A **comment** starts with `//` and runs to the end of the line. It is for the human reader; the algorithm ignores it.

```
// Swap the values of X and Y
DECLARE X, Y, Temp : INTEGER
X ← 1
Y ← 2
Temp ← X    // temporarily store X
X ← Y
Y ← Temp
OUTPUT X, " ", Y
```

Indentation shows which statements are **inside** a structure. The syllabus asks for four spaces per level, with one exception you must know:

```
DECLARE X, Y : INTEGER
X ← 7
Y ← 3
IF X > Y
    THEN
        OUTPUT "X is bigger"
    ELSE
        OUTPUT "Y is bigger or equal"
ENDIF
```

- THEN and ELSE are indented **two** spaces from their IF.
- The statements under them are indented **four**.
- ENDIF lines up with its own IF.



*Counting the spaces: 0, 2, 4*

Common mistakes

- Putting **THEN** on the IF line. That is the A-Level 9618 layout – see topic 11.
- No indentation at all. A marker has to see the structure to award the structure marks.

2 Variables, constants and types

2.1 ■ The five data types

0478 pseudocode has exactly **five** data types . Learn the list – naming a type that is not on it loses the mark.

| Type    | Holds                        | Example    |
|---------|------------------------------|------------|
| INTEGER | a whole number               | 42, -7     |
| REAL    | a number with a decimal part | 3.14, -0.5 |
| CHAR    | a single character           | 'A'        |
| STRING  | a sequence of characters     | "Hello"    |
| BOOLEAN | TRUE or FALSE                | TRUE       |

```
DECLARE Age : INTEGER
DECLARE Price : REAL
DECLARE Grade : CHAR
DECLARE Name : STRING
DECLARE Passed : BOOLEAN
Age ← 17
Price ← 2.50
Grade ← 'A'
Name ← "Mei"
Passed ← TRUE
OUTPUT Name, " is ", Age, " and passed: ", Passed
```

- A STRING is written in **double** quotes, a CHAR in **single** quotes.
- TRUE and FALSE are keywords, so they are upper case and carry no quotes.

Common mistakes

- Writing FLOAT, DOUBLE or BOOL. Those are real languages, not this syllabus.
- 'Hello' for a string – single quotes hold one character only.

The five data types

|         |                    |              |
|---------|--------------------|--------------|
| INTEGER | a whole number     | e.g. 42      |
| REAL    | a decimal number   | e.g. 3.14    |
| CHAR    | a single character | e.g. 'A'     |
| STRING  | text               | e.g. "hello" |
| BOOLEAN | true or false      | e.g. TRUE    |

The five data types: INTEGER, REAL, CHAR, STRING and BOOLEAN

2.2 ■ DECLARE

DECLARE names a variable and fixes its type before you use it.

```
DECLARE <identifier> : <data type>
```

```
DECLARE Counter : INTEGER
DECLARE TotalToPay : REAL
Counter ← 1
TotalToPay ← 19.99
OUTPUT "Item ", Counter, " costs ", TotalToPay
```

Several names of one type go on a single line, separated by commas:

```
DECLARE RoomLength, Width, Area : INTEGER
RoomLength ← 6
Width ← 4
Area ← RoomLength * Width
OUTPUT "Area = ", Area
```

- Declare a variable **before** its first use, near the top of the algorithm.
- A variable keeps its type for the whole algorithm – an INTEGER never holds "Mei".

Common mistakes

- Leaving out the colon: DECLARE Counter INTEGER.
- Using a variable that was never declared. The exam expects the declaration.

DECLARE names a variable and fixes its type

DECLARE Score : INTEGER

17

Score ← 17

DECLARE Price : REAL

4.5

Price ← 4.5

DECLARE Name : STRING

"Mia"

Name ← "Mia"

the box only accepts values of its declared type

DECLARE names a variable and fixes the type of value it can hold

2.3 ■ CONSTANT

A **constant** is a value that is fixed for the whole algorithm – a tax rate,  $\pi$ , the size of a class. Naming it once means a change is made in one place.

```
CONSTANT <identifier> ← <value>
```

```

CONSTANT TaxRate ← 0.20
DECLARE Price, Tax : REAL
Price ← 50.00
Tax ← Price * TaxRate
OUTPUT "Tax to pay: ", Tax

```

- In **0478** the arrow is used, exactly as for an assignment.
- The value must be a **literal** – a number, a string, TRUE – never a calculation and never another variable.
- A constant can never be given a new value later. That is the whole point of it.

### Common mistakes

- `CONSTANT TaxRate = 0.20`. The = form is the A-Level 9618 spelling – see topic 11.
- Assigning to a constant further down the algorithm.

## 3 Assignment, input and output

### 3.1 ■ The assignment arrow

The **assignment** operator is  $\leftarrow$ , a left-pointing arrow. It means *take the value on the right and put it in the box on the left*.


```
<identifier> ← <value>
```

```

DECLARE Counter : INTEGER
Counter ← 0
Counter ← Counter + 1
Counter ← Counter + 1
OUTPUT Counter

```

`Counter ← Counter + 1` looks impossible as mathematics and is ordinary as an instruction: work out the right-hand side with the value the box holds now, then store the result back.



*Right side first, then store into the box*

- If you cannot type  $\leftarrow$ , write `<-`. Both are accepted, here and in the exam.
- The left side must be a **single identifier** or one array element. Never a calculation.

### Common mistakes

- `Counter = 0`. In pseudocode = is a **comparison**, not an assignment – and confusing the two is the single commonest syntax error in this paper.
- `Counter + 1 ← Counter`. The arrow points at the thing being changed.

3.2 ■ INPUT and OUTPUT

INPUT reads a value from the user into a variable. OUTPUT displays one or more values.

```
DECLARE Name : STRING
DECLARE Age : INTEGER
INPUT Name
INPUT Age
OUTPUT "Hello ", Name
OUTPUT "Next year you will be ", Age + 1
```

- INPUT takes exactly **one** variable, and that variable must already be declared.
- OUTPUT takes any number of items separated by **commas**; they are printed one after another with nothing between them.
- A literal string in an OUTPUT goes in double quotes; a variable does not.

3.2.1 Prompting the user

An INPUT on its own shows nothing on screen, so a well-written algorithm prints a prompt first:

```
DECLARE Radius : REAL
OUTPUT "Enter the radius: "
INPUT Radius
OUTPUT "The diameter is ", Radius * 2
```



The prompt appears first, then the typed answer, then the reply

Common mistakes

- INPUT "Enter a number", X – the prompt is a separate OUTPUT statement.
- OUTPUT "Total: " + Total. 0478 joins output items with a comma; + is arithmetic and & belongs to A-Level 9618 (topic 11).
- Forgetting the quotes: OUTPUT Hello looks for a *variable* called Hello.

4 Arithmetic and logic

4.1 ■ Arithmetic operators

Five arithmetic operators, in the order a calculator uses them.

| Operator | Meaning          | A is 7, B is 2 |
|----------|------------------|----------------|
| +        | add              | A + B is 9     |
| -        | subtract         | A - B is 5     |
| *        | multiply         | A * B is 14    |
| /        | divide           | A / B is 3.5   |
| ^        | raise to a power | A ^ B is 49    |

```
DECLARE A, B : INTEGER
A ← 7
B ← 2
OUTPUT "Sum: ", A + B
OUTPUT "Product: ", A * B
OUTPUT "Quotient: ", A / B
OUTPUT "Power: ", A ^ B
```

Brackets come first, then ^, then \* and /, then + and - – the usual precedence. Use brackets whenever the reader would have to stop and think.

```
DECLARE Total : REAL
Total ← (12 + 18) / 2
OUTPUT "Mean: ", Total
```

Common mistakes

- Expecting / to give a whole number. 7 / 2 is 3.5, not 3; for a whole number use DIV.
- Writing A x B or A ÷ B. Use \* and /.

4.2 ■ DIV and MOD


Integer division answers two different questions, and 0478 writes each of them as a **function**, with the two values in brackets.

- DIV(a, b) – how many whole times **b** goes into **a**, the **quotient**.
- MOD(a, b) – what is left over, the **remainder**.

```
OUTPUT DIV(10, 3)
OUTPUT MOD(10, 3)
OUTPUT DIV(17, 5)
OUTPUT MOD(17, 5)
```

Both take integers, and both return an integer.

### DIV and MOD: split 17 into groups of 5



17 split into groups of 5: DIV gives the 3 whole groups, MOD the 2 left over

#### 4.2.1 What they are for

MOD is the standard test for *divides exactly*, which makes it the way to ask whether a number is even :

```
DECLARE Number : INTEGER
Number ← 12
IF MOD(Number, 2) = 0
    THEN
        OUTPUT Number, " is even"
    ELSE
        OUTPUT Number, " is odd"
ENDIF
```

DIV converts a total into whole units – seconds into minutes, pence into pounds:

```
DECLARE Seconds : INTEGER
Seconds ← 200
OUTPUT DIV(Seconds, 60), " minutes and ", MOD(Seconds, 60), " seconds"
```

#### Common mistakes

- 10 MOD 3. That is the A-Level 9618 form; **0478 uses the function form** MOD(10, 3).
- Mixing the two up. DIV gives the whole part; MOD gives what does not fit.

### 4.3 ■ Relational and logic operators

A **relational operator** compares two values and produces TRUE or FALSE.

| Operator | Means                       |
|----------|-----------------------------|
| =        | is equal to                 |
| <>       | is not equal to             |
| >        | is greater than             |
| <        | is less than                |
| >=       | is greater than or equal to |
| <=       | is less than or equal to    |

```
DECLARE Mark : INTEGER
Mark ← 55
OUTPUT "Pass: ", Mark >= 50
OUTPUT "Perfect: ", Mark = 100
OUTPUT "Not zero: ", Mark <> 0
```

The three **logic operators** join conditions:


- AND – both sides must be TRUE.
- OR – at least one side must be TRUE.
- NOT – turns TRUE into FALSE and back.

```
DECLARE Age : INTEGER
DECLARE HasTicket : BOOLEAN
Age ← 16
HasTicket ← TRUE
IF Age >= 15 AND HasTicket = TRUE
    THEN
        OUTPUT "Admitted"
    ENDIF
IF NOT (Age > 18)
    THEN
        OUTPUT "Still a student rate"
    ENDIF
```

#### Common mistakes

- <> is the *not equal* sign here – not !=, which belongs to other languages.
- IF Age >= 15 AND <= 18. Each side of AND needs its own complete comparison: Age >= 15 AND Age <= 18.
- Calling these *comparison operators* in an answer. The syllabus term is **relational**.

#### AND: both tests must be TRUE



AND needs both tests TRUE: age 14 passes both, age 10 fails the first

## 5 String operations

### 5.1 ■ LENGTH, UCASE and LCASE

0478 publishes four string routines and no others. Three of them are here.

LENGTH(<identifier>) returns how many characters a string holds – spaces included.

```
OUTPUT LENGTH("Happy Days")
OUTPUT LENGTH("")
```

UCASE(<identifier>) returns the string in upper case, LCASE(<identifier>) in lower case. Neither changes the original – each hands back a new value.

```
DECLARE Name : STRING
Name ← "Happy"
OUTPUT UCASE(Name)
OUTPUT LCASE(Name)
OUTPUT Name
```

That last line still prints Happy: to keep the change you must assign it back.

```
DECLARE Name : STRING
Name ← "Happy"
Name ← UCASE(Name)
OUTPUT Name
```

#### 5.1.1 Comparing without worrying about case

UCASE on both sides is the standard way to accept an answer however it was typed:

```
DECLARE Answer : STRING
Answer ← "yes"
IF UCASE(Answer) = "YES"
    THEN
        OUTPUT "Accepted"
ENDIF
```

#### Common mistakes

- Expecting UCASE(Name) to change Name. Assign the result back.
- LENGTH counts characters, not words. LENGTH("Happy Days") is 10.


### 5.2 ■ SUBSTRING

SUBSTRING(<identifier>, <start>, <length>) pulls a piece out of a string – starting at position **start**, taking **length** characters.

```
OUTPUT SUBSTRING("Happy Days", 1, 5)
OUTPUT SUBSTRING("Happy Days", 7, 4)
```

△ **Counting starts at 1**, not 0. The first character of "Happy Days" is at position 1.

#### SUBSTRING counts from position 1



Characters count from 1: SUBSTRING("Computer", 1, 4) gives "Comp"

#### 5.2.1 Taking one character, and the rest

```
DECLARE Word : STRING
Word ← "Computer"
OUTPUT "First letter: ", SUBSTRING(Word, 1, 1)
OUTPUT "Last letter: ", SUBSTRING(Word, LENGTH(Word), 1)
OUTPUT "Without the first: ", SUBSTRING(Word, 2, LENGTH(Word) - 1)
```

LENGTH inside SUBSTRING is what makes the last two lines work for a word of any size – hard-coding 8 would break the moment the word changed.

#### 5.2.2 Reading a string one character at a time

```
DECLARE Word : STRING
DECLARE Index : INTEGER
Word ← "Cat"
FOR Index ← 1 TO LENGTH(Word)
    OUTPUT SUBSTRING(Word, Index, 1)
NEXT Index
```

#### Common mistakes

- Starting at 0. Position 1 is the first character.
- Reading the third argument as an *end position*. It is a **count** – SUBSTRING(W, 2, 3) takes three characters beginning at the second.
- Asking for more characters than the string has.

## 6 Selection

### 6.1 ■ IF, THEN, ELSE, ENDIF

**Selection** runs one group of statements or another, depending on a condition

```
IF <condition>
  THEN
    <statements>
  ENDIF
```

```
DECLARE Mark : INTEGER
Mark ← 72
IF Mark >= 50
  THEN
    OUTPUT "Pass"
  ENDIF
```


Add ELSE for the other case. Exactly one of the two branches runs – never both, never neither.

```
DECLARE Mark : INTEGER
Mark ← 41
IF Mark >= 50
  THEN
    OUTPUT "Pass"
  ELSE
    OUTPUT "Fail"
  ENDIF
```

The layout is the one part students lose marks on, so learn it as a shape:

- IF and its condition on one line, **nothing after the condition**.
- THEN and ELSE on their own lines, indented **two** spaces.
- The statements indented **four**.
- ENDIF back at the column of its IF.

#### IF chooses one of two paths



*IF chooses one of two paths; both rejoin at ENDIF*

#### 6.1.1 Nesting

An IF inside an IF handles more than two outcomes. Each one needs its own ENDIF.

```
DECLARE Mark : INTEGER
Mark ← 85
IF Mark >= 80
  THEN
    OUTPUT "Distinction"
  ELSE
    IF Mark >= 50
      THEN
        OUTPUT "Pass"
      ELSE
        OUTPUT "Fail"
      ENDIF
    ENDIF
  ENDIF
```

#### Common mistakes

- Forgetting ENDIF. Every IF closes, and a missing one is a syntax error the marker will see at a glance.
- IF Mark >= 50 THEN OUTPUT "Pass" on one line. **No such form exists** in either syllabus; write the three lines.
- IF Mark = 50 THEN written as IF Mark ← 50. The arrow assigns; = compares.

## 6.2 ■ CASE OF


When one variable is tested against several **single values**, CASE OF says it far more clearly than a stack of nested IFs.

```
CASE OF <identifier>
  <value 1> : <statement>
  <value 2> : <statement>
  OTHERWISE <statement>
ENDCASE
```

```
DECLARE Choice : INTEGER
Choice ← 2
CASE OF Choice
  1 : OUTPUT "You chose north"
  2 : OUTPUT "You chose south"
  3 : OUTPUT "You chose east"
  4 : OUTPUT "You chose west"
  OTHERWISE OUTPUT "That is not a direction"
ENDCASE
```

- Each branch is a **value**, a colon, then what to do.
- OTHERWISE catches everything the listed values missed. It is optional, and writing one is good practice – it is what happens when the user types something unexpected.
- The first matching branch runs, and the rest are skipped.

### CASE picks the matching value



*CASE compares the value with each option in turn; Grade = 2 matches the second*

### 6.2.1 A range, and a character

```
DECLARE Grade : CHAR
Grade ← 'B'
CASE OF Grade
  'A' : OUTPUT "Excellent"
  'B' : OUTPUT "Good"
  'C' : OUTPUT "Satisfactory"
  OTHERWISE OUTPUT "Unclassified"
ENDCASE
```

#### Common mistakes

- Using CASE OF for a **condition**. It tests one variable against values; Mark >= 50 needs an IF.
- Forgetting ENDCASE.
- Leaving out OTHERWISE and then wondering why an unexpected value does nothing at all.

## 7 Iteration

### 7.1 ■ FOR, the counted loop


**Iteration** repeats statements. Use a FOR loop when you know **before you start** how many times – a count-controlled loop.

```
FOR <identifier> ← <value1> TO <value2>
    <statements>
NEXT <identifier>
```

```
DECLARE Index : INTEGER
FOR Index ← 1 TO 5
    OUTPUT "Line ", Index
NEXT Index
```

The counter starts at the first value, and the loop runs once for every value up to and **including** the second. 1 TO 5 runs five times.

**FOR Count ← 1 TO 4 repeats a set number of times**



*FOR Count ← 1 TO 4 runs four passes, and both 1 and 4 are included*

#### 7.1.1 STEP

STEP changes the size of each jump. A negative step counts down.

```
DECLARE Index : INTEGER
FOR Index ← 2 TO 10 STEP 2
    OUTPUT Index
NEXT Index
FOR Index ← 3 TO 1 STEP -1
    OUTPUT "Countdown ", Index
NEXT Index
```

#### 7.1.2 Running totals

The commonest use: a variable outside the loop that the loop adds to.

```
DECLARE Index, Total : INTEGER
Total ← 0
FOR Index ← 1 TO 10
    Total ← Total + Index
NEXT Index
OUTPUT "Sum of 1 to 10 is ", Total
```

Total ← 0 must sit **before** the loop. Inside, it would reset on every pass.

#### Common mistakes

- NEXT naming the wrong counter. Nested loops must close in the reverse order they opened: the inner NEXT first.
- Assuming 1 TO 5 runs four times. Both ends are included.
- Changing the counter inside the loop. Let FOR own it.

### 7.2 ■ WHILE, the pre-condition loop

A WHILE loop tests **before** each pass, so it can run **zero** times. Use it when the number of repeats depends on something that happens while the loop runs.

```
WHILE <condition> DO
    <statements>
ENDWHILE
```

```
DECLARE Total : INTEGER
Total ← 1
WHILE Total < 100 DO
    Total ← Total * 2
ENDWHILE
OUTPUT "First power of two past 100: ", Total
```

Something inside the loop must eventually make the condition false, or the loop never ends – an **infinite loop**.

```
DECLARE Count : INTEGER
Count ← 5
WHILE Count > 0 DO
    OUTPUT Count
    Count ← Count - 1
ENDWHILE
OUTPUT "Lift off"
```

#### Common mistakes

- Forgetting to change the variable the condition tests, giving an infinite loop.
- Leaving out DO or ENDWHILE.
- Using WHILE where the count is known. A FOR says what you mean in one line.

7.3 ■ REPEAT, the post-condition loop

A REPEAT loop tests **after** each pass, so it always runs **at least once**.

```
REPEAT
  <statements>
UNTIL <condition>
```

That “at least once” is the reason to choose it: validating input, where you must ask before you can judge the answer.


```
DECLARE Number : INTEGER
Number ← 0
REPEAT
  Number ← Number + 25
  OUTPUT "Trying ", Number
UNTIL Number >= 100
OUTPUT "Reached ", Number
```

△ UNTIL states the condition that **stops** the loop; WHILE states the one that **keeps it going**. They are opposites, and swapping them is the classic error.

|        | Tests     | Runs at least once?                 | Condition means               |
|--------|-----------|-------------------------------------|-------------------------------|
| FOR    | a counter | no (an empty range runs zero times) | –                             |
| WHILE  | before    | no                                  | keep going while this is true |
| REPEAT | after     | yes                                 | stop when this becomes true   |

Common mistakes

- Writing UNTIL Number < 100 when you mean UNTIL Number >= 100.
- Using REPEAT where the body must be able to run zero times.
- Forgetting that UNTIL ends the structure – there is no ENDREPEAT.



*WHILE tests first and may run zero times; REPEAT tests last and runs at least once*

## 8 Arrays

### 8.1 ■ One-dimensional arrays


An **array** holds many values of one type under one name. Each value sits at an **index**.

```
DECLARE <identifier> : ARRAY[<lower>:<upper>] OF <data type>
```

```
DECLARE Names : ARRAY[1:3] OF STRING
Names[1] ← "Mei"
Names[2] ← "Sam"
Names[3] ← "Ana"
OUTPUT Names[2]
```

- The bounds are written **lower:upper**, and **both are included** – [1:3] has three elements.
- Cambridge arrays normally start at **1**, not 0.
- Every element has the same type, fixed by OF.

#### A 1-D array stores many values



*A 1-D array: one name, many values, each found by its index*

#### 8.1.1 Filling and reading with a FOR loop

An array and a counted loop belong together: the counter is the index.

```
DECLARE Scores : ARRAY[1:5] OF INTEGER
DECLARE Index, Total : INTEGER
FOR Index ← 1 TO 5
    Scores[Index] ← Index * 10
NEXT Index
Total ← 0
FOR Index ← 1 TO 5
    Total ← Total + Scores[Index]
NEXT Index
OUTPUT "Total: ", Total
OUTPUT "Mean: ", Total / 5
```

#### 8.1.2 Finding the largest

```
DECLARE Scores : ARRAY[1:5] OF INTEGER
DECLARE Index, Largest : INTEGER
Scores[1] ← 42
Scores[2] ← 17
Scores[3] ← 93
Scores[4] ← 8
Scores[5] ← 55
Largest ← Scores[1]
FOR Index ← 2 TO 5
    IF Scores[Index] > Largest
        THEN
            Largest ← Scores[Index]
        ENDIF
NEXT Index
OUTPUT "Largest: ", Largest
```

Start **Largest** at the **first element**, never at 0 – with negative data, 0 would win and the answer would be wrong.

#### Common mistakes

- Reading Scores[6] from an array declared [1:5]. That is out of bounds.
- Writing Scores(3). Arrays use square brackets; round brackets call a function.
- Declaring [1:5] and then looping 0 TO 4.


8.2 ■ Two-dimensional arrays

A **2-D array** is a table: rows and columns, two indexes.

```
DECLARE <identifier> : ARRAY[<lower1>:<upper1>, <lower2>:<upper2>] OF
↳ <data type>

DECLARE Grid : ARRAY[1:2, 1:3] OF INTEGER
Grid[1,1] ← 1
Grid[1,2] ← 2
Grid[1,3] ← 3
Grid[2,1] ← 4
Grid[2,2] ← 5
Grid[2,3] ← 6
OUTPUT Grid[2,3]
```

The **first** index is the row, the **second** the column.



A 2-D array is a grid: G[1, 2] is row 1, column 2

8.2.1 Nested loops walk a table

One loop per dimension. The inner loop finishes a whole row before the outer moves on.

```
DECLARE Grid : ARRAY[1:2, 1:3] OF INTEGER
DECLARE Row, Col : INTEGER
FOR Row ← 1 TO 2
  FOR Col ← 1 TO 3
    Grid[Row, Col] ← Row * Col
  NEXT Col
NEXT Row
FOR Row ← 1 TO 2
  FOR Col ← 1 TO 3
    OUTPUT "Grid[" , Row, ", " , Col, "] = " , Grid[Row, Col]
  NEXT Col
NEXT Row
```

△ The inner NEXT closes the **inner** counter. NEXT Row before NEXT Col crosses the loops over and is nonsense – a marker spots it instantly.

Common mistakes

- Swapping row and column. Grid[2,3] is row 2, column 3.
- Grid[Row] [Col]. Cambridge writes **one** pair of brackets with a comma inside.
- Crossing the NEXT lines over, as above.

## 9 Procedures and functions

### 9.1 ■ PROCEDURE and CALL

A **procedure** is a named block of statements. Writing one once and calling it from several places is **decomposition** – the idea the whole of paper 2 rests on.

```
PROCEDURE <identifier>
  <statements>
ENDPROCEDURE
```

A procedure is **called** by name, with the keyword CALL:

```
PROCEDURE DefaultLine
  OUTPUT "-----"
ENDPROCEDURE

CALL DefaultLine
OUTPUT "Report"
CALL DefaultLine
```

- The definition does nothing on its own. Only CALL runs it.
- Control returns to the line after the CALL when the procedure ends.
- A procedure **does not give a value back**. If you need one, you want a function.

#### Common mistakes

- Writing DefaultLine on its own to run it. 0478 requires CALL.
- Leaving out ENDPROCEDURE.
- Expecting the procedure's own variables to exist outside it.

### 9.2 ■ FUNCTION and RETURN

A **function** is a named routine that returns a value. It is written where that value is needed – inside an OUTPUT, on the right of an assignment, inside a condition.

```
FUNCTION <identifier>(<parameters>) RETURNS <data type>
  <statements>
  RETURN <value>
ENDFUNCTION
```

```
FUNCTION SumSquare(Number1 : INTEGER, Number2 : INTEGER) RETURNS INTEGER
  RETURN Number1 * Number1 + Number2 * Number2
ENDFUNCTION
```

```
OUTPUT "Sum of squares = ", SumSquare(10, 20)
```

- RETURNS <data type> on the header says what type comes back. It is not optional.
- RETURN ends the function **immediately** – nothing after it runs.
- A function is **never** called with CALL; it is used wherever its value belongs.



*A procedure is CALLED to do a job; a function returns a value to use*

#### 9.2.1 A function inside a condition

```
FUNCTION IsEven(Number : INTEGER) RETURNS BOOLEAN
  RETURN MOD(Number, 2) = 0
ENDFUNCTION

DECLARE Index : INTEGER
FOR Index ← 1 TO 6
  IF IsEven(Index)
    THEN
      OUTPUT Index, " is even"
    ENDIF
NEXT Index
```

#### Common mistakes

- CALL SumSquare(10, 20) – that throws the answer away.
- A function with no RETURN on some path. Every route out must return a value.
- Leaving RETURNS INTEGER off the header.

9.3 ■ Parameters

A **parameter** is a value a procedure or function is given when it is called. Each one carries its own type.

```
PROCEDURE Line(Size : INTEGER)
  DECLARE Index : INTEGER
  FOR Index ← 1 TO Size
    OUTPUT "-"
  NEXT Index
ENDPROCEDURE

CALL Line(5)
CALL Line(20)
```

Several parameters are separated by commas, and the order at the call must match the order in the definition:

```
PROCEDURE Greet(Name : STRING, Times : INTEGER)
  DECLARE Index : INTEGER
  FOR Index ← 1 TO Times
    OUTPUT "Hello ", Name
  NEXT Index
ENDPROCEDURE

CALL Greet("Mei", 2)
CALL Greet("Sam", 1)
```

△ In 0478 every parameter is passed by value : the procedure works on a copy, so changing it inside changes nothing outside. To get a value back, use a FUNCTION and RETURN it. (A-Level 9618 adds BYREF for the other behaviour – topic 11.)

```
FUNCTION Doubled(Number : INTEGER) RETURNS INTEGER
  RETURN Number * 2
ENDFUNCTION

DECLARE Value : INTEGER
Value ← 7
Value ← Doubled(Value)
OUTPUT Value
```

Common mistakes

- PROCEDURE Line(Size) with no type.
- Calling with the arguments in the wrong order – Greet(2, "Mei") is a type error.
- Expecting a procedure to change the variable you passed in. In 0478 it cannot.

10 File handling

10.1 ■ Writing to a file

A file keeps data after the program ends. 0478 uses four commands, and every one names the file it works on.

```
OPENFILE <file identifier> FOR WRITE
WRITEFILE <file identifier>, <data>
CLOSEFILE <file identifier>
```

```
OPENFILE "names.txt" FOR WRITE
WRITEFILE "names.txt", "Mei"
WRITEFILE "names.txt", "Sam"
CLOSEFILE "names.txt"
OUTPUT "Saved"
```

Three file modes :

| Mode   | What it does                                             |
|--------|----------------------------------------------------------|
| WRITE  | start a new file – <b>anything already there is lost</b> |
| APPEND | add to the end of what is there                          |
| READ   | read from the start                                      |

```
OPENFILE "log.txt" FOR WRITE
WRITEFILE "log.txt", "first"
CLOSEFILE "log.txt"
OPENFILE "log.txt" FOR APPEND
WRITEFILE "log.txt", "second"
CLOSEFILE "log.txt"
OUTPUT "Both lines saved"
```

- One WRITEFILE writes **one line**.
- CLOSEFILE is not optional. An unclosed file can lose the data still waiting to be written, and that is a stock exam answer.

Common mistakes

- FOR WRITE when you meant FOR APPEND, which silently destroys the old contents.
- Forgetting CLOSEFILE.
- Opening a file that is already open.

## 10.2 ■ Reading a file to the end

READFILE takes one line into a variable. The variable must be declared first.

```
OPENFILE <file identifier> FOR READ
READFILE <file identifier>, <variable>
CLOSEFILE <file identifier>
```

Normally you do not know how many lines there are, so you read **until the end of the file** – which is what the EOF function reports.

```
OPENFILE "names.txt" FOR WRITE
WRITEFILE "names.txt", "Mei"
WRITEFILE "names.txt", "Sam"
WRITEFILE "names.txt", "Ana"
CLOSEFILE "names.txt"

DECLARE Line : STRING
OPENFILE "names.txt" FOR READ
WHILE NOT EOF("names.txt") DO
    READFILE "names.txt", Line
    OUTPUT Line
ENDWHILE
CLOSEFILE "names.txt"
```

EOF("names.txt") is TRUE once every line has been read, so WHILE NOT EOF(...) means *while there is still something to read*.

### Text files: open, read or write, close

|                                 |                               |
|---------------------------------|-------------------------------|
| OPENFILE "Scores.txt" FOR WRITE | WRITE starts an empty file    |
| WRITEFILE "Scores.txt", Line    | adds one line                 |
| OPENFILE "Scores.txt" FOR READ  | READ starts at the first line |
| READFILE "Scores.txt", Line     | reads the next line into Line |
| CLOSEFILE "Scores.txt"          | always close when finished    |

the data stays in the file after the program ends

*Open a file for WRITE or READ, use it line by line, then close it*

## 10.2.1 Counting while reading

```
OPENFILE "marks.txt" FOR WRITE
WRITEFILE "marks.txt", 40
WRITEFILE "marks.txt", 65
WRITEFILE "marks.txt", 88
CLOSEFILE "marks.txt"

DECLARE Mark, Count, Total : INTEGER
Count ← 0
Total ← 0
OPENFILE "marks.txt" FOR READ
WHILE NOT EOF("marks.txt") DO
    READFILE "marks.txt", Mark
    Count ← Count + 1
    Total ← Total + Mark
ENDWHILE
CLOSEFILE "marks.txt"
OUTPUT Count, " marks, mean ", Total / Count
```

### Common mistakes

- A WHILE EOF(...) loop – that runs only when there is nothing left. You want NOT.
- Reading past the end because the loop has no EOF guard.
- Opening FOR READ a file that was never written.

11 A-Level 9618: what changes

11.1 ■ Layout and operators

Cambridge publishes **two** pseudocode specifications, and they disagree. Everything in topics 1-10 is **IGCSE 0478**. A-Level **9618** changes the details below – and a student who studies both loses marks by writing one in the other’s paper.

|                 | IGCSE 0478                          | A-Level 9618          |
|-----------------|-------------------------------------|-----------------------|
| THEN            | on its <b>own line</b> , indented 2 | on the <b>IF line</b> |
| constants       | CONSTANT Pi ← 3.142                 | CONSTANT Pi = 3.142   |
| DIV / MOD       | functions: DIV(10, 3)               | operators: 10 DIV 3   |
| joining strings | commas in OUTPUT                    | the & operator        |
| identifiers     | must start with a <b>capital</b>    | mixed case allowed    |
| NEXT            | must name its counter               | good practice         |
| ROUND, RANDOM() | both published                      | <b>neither</b> exists |

This is the 0478 form, and it runs here:

```
DECLARE Total : REAL
CONSTANT Rate ← 0.5
Total ← 10
IF MOD(7, 2) = 1
    THEN
        OUTPUT "Odd, half rate ", Total * Rate
ENDIF
```

The 9618 form of the same algorithm is written like this – note THEN on the IF line, = in the CONSTANT, and MOD between its two values:

```
DECLARE Total : REAL
CONSTANT Rate = 0.5
Total ← 10
IF 7 MOD 2 = 1 THEN
    OUTPUT "Odd, " & "half rate ", Total * Rate
ENDIF
```

△ **Which one is right depends only on which paper you are sitting.** Neither is a mistake; each is a mistake in the other’s exam. The playground on this page runs the **0478** rules, so a 9618 construct is refused with a message naming the syllabus it belongs to – which is a quick way to check your own habits.

Common mistakes

- Writing THEN on the IF line in an 0478 answer, because that is what a textbook or a website showed. It is the single commonest cross-syllabus slip.
- 10 MOD 3 in 0478. There it is MOD(10, 3).
- ROUND(3.14159, 2) in a 9618 answer. 9618 has no ROUND at all.

11.2 ■ Parameters: BYVAL and BYREF

0478 passes **every** parameter by value (topic 9). 9618 lets you choose, and says so in the header.

- BYVAL – the procedure gets a **copy**. Changing it changes nothing outside. This is the default when neither word is written.
- BYREF – the procedure works on the caller’s **own variable** by reference, so a change is visible after the call.

This is 9618 only. It does not run here, and it is not accepted in an 0478 answer:

```
PROCEDURE Increase(BYREF Value : INTEGER)
    Value ← Value + 1
ENDPROCEDURE

DECLARE Count : INTEGER
Count ← 5
CALL Increase(Count)
OUTPUT Count // prints 6
```

BYVAL copies the value; BYREF shares the variable



*BYVAL passes a copy; BYREF lets the procedure change the caller’s variable*

11.2.1 The 0478 way to get a value back

Use a FUNCTION and assign what it returns. This is the whole of the 0478 answer, and it runs:

```
FUNCTION Increased(Value : INTEGER) RETURNS INTEGER
    RETURN Value + 1
ENDFUNCTION

DECLARE Count : INTEGER
Count ← 5
Count ← Increased(Count)
OUTPUT Count
```

Common mistakes

- Writing BYREF in an 0478 answer. The keyword is not in that syllabus.
- Expecting a plain 9618 parameter to behave like BYREF. Without the word it is BYVAL.

11.3 ■ Records and other types

9618 has data structures that 0478 does not. You will meet them only at A-Level, and none of them runs under the 0478 rules of this page.

A **record** groups fields of different types under one name (9618 section 4):

```
TYPE Student
  DECLARE Name : STRING
  DECLARE Mark : INTEGER
ENDTYPE

DECLARE Candidate : Student
Candidate.Name ← "Mei"
Candidate.Mark ← 91
OUTPUT Candidate.Name, " scored ", Candidate.Mark
```

An **enumerated type** lists the only values a variable may take:

```
TYPE Vehicle = (Car, Bus, Taxi)
DECLARE MyRide : Vehicle
MyRide ← Taxi
```


9618 also adds a DATE data type, random-access files (OPENFILE ... FOR RANDOM), pointers, and classes with CLASS ... ENDCLASS for its object-oriented paper.

△ 0478 has **five** data types and arrays, and nothing else (topic 2). A 0478 answer that declares a record is answering a different syllabus.

Common mistakes

- Using a record in an 0478 answer. Use parallel arrays instead – one array per field, sharing an index.
- Thinking TYPE means the same as DECLARE. TYPE defines a **new type**; DECLARE creates a **variable** of an existing one.

A record groups fields of different types



*A record groups fields of different types; dot notation reaches each one*