

4.3 Composition and inheritance

Name: _____ Class: _____ Date: _____

Total: 24 marks

KEY WORDS inheritance • composition

Objective

Choose composition or inheritance with a stated reason, trace initialisation chains, and repair a fragile base.

1 Key knowledge and worked examples

■ Base first

`Member.__init__` opens with `super().__init__(name)`, so `Person.__init__` completes before any `Member` line runs ✓. Skip the call and the base attribute does not exist when the derived class needs it ✓.

■ Worked example: the stale fork

A base `total` gains a loyalty line; the subclass that copied the summing code silently loses the bonus, while the subclass that wrote `super().total() - 10` keeps it ✓. Override by delegating, never by duplicating ✓.

2 Practice

2.1 A `Member(Person)` is constructed. State which `__init__` body completes first and why. [3]

2.2 Choose the connection: a `Library` and its `Catalog`. Name the relation and the arrow that draws it. [3]

2.3 A subclass override duplicates the base body instead of delegating. State the one-line repair. [3]

3 Exam-style questions

3.1 A system has: **Person**, **Member** (a person with a card and a loan count), **Library**, and **Catalog** (the list of copies a library owns).

State which pairs join by inheritance and which by composition, with a reason each. Write the **Member** constructor so base state exists before any derived line runs, naming the call that guarantees it. State what the library's **available** count reads after 5 copies are added and 2 issued, and which object answers the question. [8]

3.2 A base **Receipt.total()** sums items. **DiscountReceipt** overrides it by copying the summing code and subtracting 10. The base then gains a loyalty bonus of 2, and items total 7.

Compute what each class's **total** now returns, and the value the discount receipt should return. Name the hazard and write the one-line repair, explaining why the repair survives future base changes. [7]

Solutions

2.1

- `Person.__init__` completes first ✓.
- The derived constructor opens with the **super** call, chaining construction base-first ✓.

2.2

- Composition (has-a) ✓.
- Drawn as a filled diamond at the whole ✓.

2.3

- Delegate: call the base method and subtract – e.g. `return super().total() - 10` ✓.

3.1

- **Member–Person**: inheritance – a member is a person ✓.
- **Library–Catalog**: composition – the library owns its catalog ✓.
- Constructor opens with the **super** call before touching derived state ✓.
- `available` reads 3: 5 added, 2 out ✓.
- Each **Copy** answers for itself; the catalog aggregates – the whole forwards the question to its parts ✓.

3.2

- Base returns $7 + 2 = 9$ ✓.
- The copied fork returns $7 - 10 = -3$, losing the bonus ✓.
- Should return $9 - 10 = -1$ ✓.
- The hazard is the fragile base class; repair: delegate via the base call and subtract ✓. Delegation re-uses whatever the base becomes, so future base lines flow through.