

5.2 Lists, stacks and queues

Name: _____ Class: _____ Date: _____

Total: 24 marks

KEY WORDS stack • queue

Objective

Price the ends of the linear structures and trace them.

1 Key knowledge and worked examples

■ The layouts

An array indexes in one computed step but slides on front inserts; a linked list splices cheaply but walks to index ✓. A stack serves one end; a queue has two ends ✓.

■ Worked example: append amortises, front never does

Doubling regrows make **append** amortized $O(1)$: each element is copied at most once overall ✓. But 100 front inserts move $100 + 99 + \dots + 1 = 5\,050$ elements – $\Theta(n^2)$ ✓.

2 Practice

2.1 push 4, push 9, push 2, pop, push 7 – give the two pops that a further pop, pop returns. [3]

2.2 State the number of element moves for n front-inserts into an initially empty array, as a formula and at $n = 200$. [3]

2.3 Enqueue x, y, z, dequeue twice – name the front element. [3]

3 Exam-style questions

3.1 A queue is built on a Python list using `append` for enqueue and `pop(0)` for dequeue.

State the cost class of each operation and of n paired enqueue-dequeue rounds. Rebuild it on `collections.deque` and state both costs again. Give the total class ratio between the two designs at $n = 10^4$, with the reason the list version loses. [8]

3.2 The bracket validator pushes opening brackets and matches each closer against the top of the stack.

Trace the scan of `{ [ ] ( ) }` listing the stack after each character. Trace `( [ ) ]` and name the character and the mismatch that fails. State the empty-stack case and why it also fails. [7]

Solutions

2.1

- The pop removed 2; the stack reads 4, 9, 7 (bottom to top) ✓.
- The next pops return 7 then 9 ✓.

2.2

- Moves = $n(n+1)/2$ ✓.
- At $n = 200$: $201 \times 100 = 20\,100$ ✓.

2.3

- z ✓.
- Dequeues removed x then y , leaving z at the front ✓.

3.1

- List: enqueue $O(1)$ amortized; **pop**(0) slides all residents, $O(n)$ ✓.
- n rounds on the list: $\Theta(n^2)$ ✓.
- Deque: both ends $O(1)$; n rounds $\Theta(n)$ ✓.
- Ratio at $n = 10^4$: quadratic versus linear – the list moves about $10^8/2$ elements where the deque moves none per pop ✓.

3.2

- $\{ [] () \}$: after $\{ \rightarrow \{;$ $[\rightarrow \{ [;]$ pops $]; (\rightarrow \{ (;)$ pops $(; \}$ pops $\{$ – empty at the end: balanced ✓.
- $([)]$: stack after $([;$ the $)$ finds $[$ on top – mismatch at $)$ (expected $]$) ✓.
- A closer arriving at an empty stack fails: nothing to match ✓.