

8.1 Relational modelling

Name: _____ Class: _____ Date: _____

Total: 24 marks

KEY WORDS primary key • foreign key

Objective

Model a domain as tables, keys and junctions, and read the ER diagram both ways.

1 Key knowledge and worked examples

■ The mapping rules

Entities to tables; one-to-many becomes a foreign key on the many side; many-to-many becomes a junction table of foreign-key pairs ✓. The engine enforces referential integrity on every foreign key ✓.

■ Worked example: the sample data

8 students, 6 courses, 14 enrollments: Student joins Enrollment joins Course joins Department yields 14 rows before any WHERE ✓.

2 Practice

2.1 A department has one building. Name the table that should carry the column, and why. [3]

2.2 Model enrolls-in as a many-to-many: give the junction table's two foreign keys. [3]

2.3 State what referential integrity forbids, in one sentence. [3]

3 Exam-style questions

3.1 A cinema domain: Customer, Film, Screening (a film shown in a room at a time), Ticket.

Identify the entities and give a one-to-many and a many-to-many relationship with their table treatments. Choose a sensible primary key for Ticket and justify it against the alternative of a surrogate ID. State the rule a composite key on Ticket would need to enforce one seat per screening. [8]

3.2 The enrolment schema stores PRIMARY KEY (`student_id`, `course_id`, `term`) on Enrollment.

Explain what this key rejects, with the exact duplicate it stops. State what is lost if the key is dropped and only the application checks duplicates. Give the two foreign keys the table also needs and what each protects. [7]

Solutions

2.1

- Department – one value per department, so it lives on the one side ✓.

2.2

- `student_id` referencing Student and `course_id` referencing Course ✓.

2.3

- No referencing row may name a target row that does not exist ✓.

3.1

- Entities: Customer, Film, Screening, Ticket ✓.
- One-to-many: Screening to Ticket – `ticket.screening_id` foreign key ✓.
- Many-to-many: Customer to Film through Ticket (a customer watches many films; a film gathers many customers) ✓.
- Key for Ticket: (`screening_id`, `seat_no`) identifies one seat at one showing – natural and duplicate-proof ✓.
- Surrogate alternative: a `ticket_id` is stable if seats get renumbered and carries no meaning to maintain ✓.
- Composite rule: PRIMARY KEY (`screening_id`, `seat_no`) rejects a second sale of the same seat ✓.

3.2

- It rejects a second row with the same (student, course, term) – the same student enrolling twice in one term ✓.
- Dropped: two racing applications both check-then-insert and both succeed – the engine no longer guarantees it ✓.
- Foreign keys: `student_id` (every enrollment names a real student) and `course_id` (a real course) ✓.