

8.3 Normalisation

Name: _____ Class: _____ Date: _____

Total: 24 marks

KEY WORDS functional dependency • third normal form

Objective

Split tables along their functional dependencies and name the form.

1 Key knowledge and worked examples

■ The forms

2NF removes part-key dependencies; 3NF removes transitive ones; BCNF makes every determinant a key ✓. The anomalies – insert, update, delete – are the symptoms of a repeated fact ✓.

■ Worked example: the split

Enroll(student, course, title, dept, building): course → title part-key, title → dept → building transitive – three tables, each fact once, each anomaly gone ✓.

2 Practice

2.1 In Enroll(student, course, title), name the part-key dependency. [3]

2.2 Deleting the last enrollment for a course also deletes the course's title. Name the anomaly. [3]

2.3 A table in BCNF is automatically in which lower forms? [3]

3 Exam-style questions

3.1 Project(proj_id, dept, dept_head, member, hours) with key (proj_id, member) and facts: each project belongs to one department; each department has one head.

List every functional dependency. Identify the part-key and the transitive dependency. Split to 3NF (give the tables), and state which anomaly each split removes. Name the form of the original table. [8]

3.2 A report stores order_id, line_no, product, unit_price, qty, order_total with key (order_id, line_no); the total is the sum of qty x unit_price over the order's lines.

Name the derivable column and the anomaly it invites. State the 3NF treatment and the cost it adds per read of the report. Give the condition under which keeping the total is the better engineering choice, naming the mechanism that keeps it honest. [7]

Solutions

2.1

- `course` $\rightarrow$ `title` – the course determines the title from part of the key (`student`, `course`) ✓.

2.2

- The delete anomaly – the fact rides on the last row carrying it ✓.

2.3

- 2NF and 3NF (BCNF implies both) ✓.

3.1

- FDs: (`proj_id`, `member`) $\rightarrow$ `hours`; `proj_id` $\rightarrow$ `dept`; `dept` $\rightarrow$ `dept_head` ✓.
- Part-key: `proj_id` $\rightarrow$ `dept` (`dept` depends on half the key); transitive: `proj_id` $\rightarrow$ `dept` $\rightarrow$ `dept_head` ✓.
- 3NF split into three tables ✓: `Project(proj_id, dept)`; `Dept(dept, dept_head)`; `Work(proj_id, member, hours)`.
- The splits remove the update anomaly (department facts stored once) and the insert anomaly (a department with no project becomes insertable) ✓.
- Original form: 1NF only (it violates 2NF) ✓.

3.2

- Derivable: `order_total` (sum over lines) ✓.
- Anomaly: update anomaly – one line changes and every stored total must change with it; miss one and the report lies ✓.
- 3NF treatment: drop the column; compute the total per read with an aggregation – the cost is a GROUP BY over the order's lines ✓.
- Keep it when the report is read far more often than lines change and the aggregation is measurably too slow – maintained by a trigger (or materialised-view refresh), the mechanism that keeps it honest ✓.