11.2 Context-free languages and parsing theory

Name: _____ Class: _____ Date: _____ **Total: 24 marks**

KEY WORDS parse tree • ambiguity

Objective

Derive with CFGs, count parse trees, and know the next ceiling.

1 Key knowledge and worked examples

■ **The grammar**

$E \to E + T \mid T$; $T \to T \times F \mid F$; $F \to (E) \mid$ **id** ✓. Layering enforces precedence ✓.

■ **Worked example: two trees**

Unlayered $E \to E + E \mid E \times E \mid$ **id** parses `id + id * id` twice (suite-counted); layered parses it once ✓.

2 Practice

2.1 Leftmost derivation of `id + id * id` under the layered grammar: how many steps? [3]

2.2 What does ambiguity mean, exactly? [3]

2.3 Why does $a^n b^n c^n$ exceed context-free power? [3]

exercises.lol exercises.com.cn

3 Exam-style questions

3.1 Under the layered grammar, write the full leftmost derivation of `id * (id + id)`.

Give each step. State which production each step applies and why that one is forced (lookahead reasoning). Draw or describe the parse tree's shape and count its leaves. State the tree's verdict on the value of `id * (id + id)` versus `(id * id) + id`. [8]

3.2 The unlayered grammar $E \to E + E \mid E \times E \mid \mathbf{id}$.

Give both parse trees for `id + id * id` (structure only). Count the trees for `id + id + id` and explain the count. State the danger ambiguity poses to a code generator, and the layered fix with its cost. [7]

exercises.lol exercises.com.cn