5.1 Asymptotic analysis

Name: _____ Class: _____ Date: _____ **Total: 24 marks**

KEY WORDS Big-O O • Big-Θ Θ

Objective

Classify algorithms by growth, and prove the class by doubling.

1 Key knowledge and worked examples

■ The classes

Drop constants and lower-order terms: $3n^2 + 5n + 7$ is $\Theta(n^2)$ ✓. At $n = 1000$: $n \log_2 n \approx 9\,966$ against $n^2 = 10^6$ – a factor of about 100 ✓.

■ Worked example: doubling reads the exponent

Nested loops at $n = 100$ run their body 10 000 times; at $n = 200$, 40 000 ✓. The ratio 4 is the exponent: the same doubling turns a linear loop's 100 into 200 ✓.

2 Practice

2.1 State the class of $7n \log_2 n + 2n + 40$, naming the rule you applied. [3]

2.2 A halving loop starts at $n = 1024$. State how many iterations to reach 1. [3]

2.3 Give the $\log_2$ values for $n = 10$, 100, 1000, rounded to integers. [3]

exercises.lol exercises.com.cn

3 Exam-style questions

3.1 Two programs run on the same machine. Program A performs $100n$ operations; program B performs $2n^2$ operations.

State the size n at which B first overtakes A (solve $2n^2 = 100n$). Classify each program, justifying by the dominant term. State which program you run at $n = 10$ and which at $n = 1000$, with the operation counts at both sizes for each program. [8]

3.2 A loop runs `while i > 1: i = i // 2` and inside it a second loop runs n times.

State what each loop contributes and multiply them into one class. Compare its cost at $n = 1024$ with a pure n^2 loop at the same n, computing both values. Explain in one line why halving produces a logarithm. [7]

exercises.lol exercises.com.cn