

University Computer Science

Name: _____ Score: _____

1. What does `'print("3" + "4")'` show?

2. What does `'print(3 >= 3 and not (2 > 5))'` show?

3. How many times does the block of `'for i in range(3, 8):'` run?

4. Which contract lets another calculation use the fee-inclusive amount directly?

- ☐ Return the fee-inclusive amount
- ☐ Ask the caller to read the terminal
- ☐ Print the amount and return nothing explicitly

5. With `'s = [10, 20, 30, 40, 50]'`, what is `'s[1:4]'`?

6. A file holds three lines: `'Ana,72'`, `'Ben,55'`, `'Cai,90'`. The loop adds `'int(line.strip().split(",")[1])'` for every line. What is the total?

7. Which split of a "print a receipt" program is the best decomposition?

- ☐ One function per line of the receipt
- ☐ One function that reads, calculates and prints everything
- ☐ Two functions, the first half and the second half of the code
- ☐ `read_items`, `line_total`, `order_total`, `format_receipt`, each doing one job

8. What is the value of `'17 % 5'`?

9. A line that is not indented, written straight after an `'if'` block, runs only when the condition is `'True'`.

- ☐ True ☐ False

10. After `'total = 0'` and `'for p in [4, 8, 15]: total += p'`, what is `'total'`?

University Computer Science

1. **34**

Both values are strings, so '+' joins them. Only numbers would give '7'.

2. **True**

'3 >= 3' is 'True'; '2 > 5' is 'False', so 'not (2 > 5)' is 'True'. Both sides are true, so 'and' gives 'True'.

3. **5**

'i' takes '3, 4, 5, 6, 7'; the end value 8 is left out. 'range(a, b)' runs $b - a = 8 - 3 = 5$ times.

4. **Return the fee-inclusive amount**

A returned result can be used in an expression; printed output is a separate side effect.

5. **[20, 30, 40]**

Position 1 holds 20 (counting from 0), and the slice stops before position 4, so it takes positions 1, 2 and 3.

6. **217**

$72 + 55 + 90 = 217$. 'strip()' removes the '"\n"', 'split(",")' separates the name from the mark, and '[1]' takes the mark.

7. **read_items, line_total, order_total, format_receipt, each doing one job**

Each piece has one job and a clear input and output, so each can be tested alone. Splitting by position in the code gives pieces with no clear contract.

8. **2**

'%' gives the remainder: $17 = 3 \times 5 + 2$, so '17 % 5' is '2' and '17 // 5' is '3'.

9. **False**

Only indented lines belong to the 'if'. The first line back at the left edge is outside the block, so it runs either way.

10. **27**

The total goes $0 \rightarrow 4 \rightarrow 12 \rightarrow 27$, one step for each item in the list.