

University Computer Science

Name: _____ Score: _____

1. Instance attributes come from –
 - ☐ copying the class attributes
 - ☐ assignments to self, usually in `__init__`
 - ☐ the caller of the method
 - ☐ the class statement itself
2. Calling `issue()` on a copy that is already out –
 - ☐ deletes the copy
 - ☐ raises, and the state is unchanged
 - ☐ returns `False` quietly
 - ☐ silently issues it again
3. `Member.__init__` starts with `super().__init__(name)` so that –
 - ☐ the name is discarded
 - ☐ the card number is inherited
 - ☐ `Person` state exists before any `Member` line runs
 - ☐ `Member` runs before `Person`
4. A Protocol names –
 - ☐ the memory address of the object
 - ☐ the test file for the class
 - ☐ the behaviour any fitting type must provide
 - ☐ the concrete class to inherit
5. `except RenewalError` catches a raised `LimitError` because –
 - ☐ their messages match
 - ☐ `except` catches everything
 - ☐ `LimitError` is its subclass
 - ☐ both are strings
6. A test that asserts the private field `loan.__days` is a good behaviour test.
 - ☐ True ☐ False

7. A class attribute is copied into each instance when the instance is created.

☐ True ☐ False

8. In Python, a leading underscore stops other code from changing the attribute.

☐ True ☐ False

9. `Receipt.total()` gave 100. The base then gains a loyalty line that takes off 5. `DiscountReceipt.total()` is written as `super().total() - 10`. What does it return now?

10. To be used where a Notifier Protocol is expected, a class must inherit from Notifier.

☐ True ☐ False

University Computer Science

1. **assignments to self, usually in `__init__`**

`__init__` runs at construction and seeds each instance its own attribute values.

2. **raises, and the state is unchanged**

The guard raises before any change is made – check-first means failed calls corrupt nothing.

3. **Person state exists before any Member line runs**

The chain is base-first: skip `super()` and `self._name` does not exist yet when Member needs it.

4. **the behaviour any fitting type must provide**

It is a structural contract: any object with the named methods fits, no inheritance needed.

5. **LimitError is its subclass**

Handlers match by type through the hierarchy: a parent except catches every child.

6. **False**

It pins storage, not a promise, so it breaks on refactors. Assert what the caller sees, such as the returned days.

7. **False**

It stays on the class, and every instance reads that one shared value.

8. **False**

It is only a convention that says "internal". Nothing stops a caller, so the discipline matters.

9. **85**

The base now gives 95, and the override subtracts 10 from that. A copied body would still say 90.

10. **False**

A Protocol is structural. Any class with a matching send method fits, with no inheritance.