

Exercise walk-through

13.6

Evaluation and leakage


University Computer Science

Evaluation and leakage: the honesty apparatus

- 1 **Matrix** TP 36, FP 10, FN 6, TN 148 on test 200: **accuracy** 0.92, **precision** 0.783, **recall** 0.857, F1 0.818 - base rate 21% makes 0.92 meaningful.
- 2 **Folds** 5-fold CV: 0.905 0.925 0.915 0.900 0.935 - mean 0.916 sd 0.013; a rival at 0.921 is within noise.
- 3 **Leak** A midnight status-code feature encodes the label: 0.99 train, 0.90 honest - the data card provenance column is the defence.

Split and confusion matrix

the split: test is spent once



5 folds over train+validation:

0.905 0.925 0.915 0.900 0.935

mean 0.916, sd 0.013

base rate 21% - the trivial predictor
scores 0.79: 0.92 means something

the matrix, and its metrics

	pred late	pred on-time	
true late	36	6	accuracy 0.92
true on-time	10	148	precision 0.783
			recall 0.857
			F1 0.818

TP 36, FP 10, FN 6, TN 148

leakage is plumbing: a midnight status code

encodes the label - a score without folds is an anecdote

The split with test spent once; the matrix with its metrics.

Exercises 2.1-2.3

2.1 What does spending the test set mean? [3]

2.2 Give the accuracy of the trivial always-on-time predictor. [3]

2.3 Name the three plumbing leakages this unit lists. [3]

Exercises 2.1-2.3

2.1 What does spending the test set mean? [3]

2.1

- Using it for model choice: it becomes a second validation set, and its score is then optimistic ✓.

2.2 Give the accuracy of the trivial always-on-time predictor. [3]

2.2

- Predicting every parcel on time: $158/200 = 0.79$ ✓.

2.3 Name the three plumbing leakages this unit lists. [3]

2.3

- Scaling before splitting; imputing with test statistics; feature selection over the full data (and the label-encoding feature itself) ✓.

Exercise 3.1

3.1 A competitor reports: TP 40, FP 20, FN 2, TN 138 on the same 200-record test set.

Compute accuracy, precision, recall, and F1 for the competitor. Compare with the course model on each metric and state which model you would deploy for catching lates, with the reason. State what additional resampling evidence you would demand before trusting either.

[8]

Exercise 3.1

3.1 A competitor reports: TP 40, FP 20, FN 2, TN 138 on the same 200-record test set.

Compute accuracy, precision, recall, and F1 for the competitor. Compare with the course model on each metric and state which model you would deploy for catching lates, with the reason. State what additional resampling evidence you would demand before trusting either. [8]

3.1

- Competitor: accuracy $(40 + 138)/200 = 0.89$ ✓.
- Precision $40/60 = 0.667$; recall $40/42 = 0.952$; $F1 = 2 \times 0.667 \times 0.952 / (0.667 + 0.952) = 0.784$ ✓.
- Comparison: competitor wins recall (0.952 vs 0.857), loses precision (0.667 vs 0.783) and accuracy (0.89 vs 0.92) ✓.
- For catching lates (refunds depend on not missing them): the competitor – recall is the operative metric ✓.
- Demand: 5-fold CV with per-fold counts, and the same folds for both models ✓.

Exercise 3.2

3.2 Design the leakage defence for a pipeline that scales features, imputes missing values, and selects features.

State the wrong order (all three before splitting) and what leaks at each step. Give the correct per-fold order. Explain the midnight status-code example in this vocabulary. State why fold metrics are averaged over per-fold counts, not over fold accuracies alone when folds are unequal. [7]

Exercise 3.2

3.2 Design the leakage defence for a pipeline that scales features, imputes missing values, and selects features.

State the wrong order (all three before splitting) and what leaks at each step. Give the correct per-fold order. Explain the midnight status-code example in this vocabulary. State why fold metrics are averaged over per-fold counts, not over fold accuracies alone when folds are unequal. [7]

3.2

- Wrong order: fit scaler, imputer, and feature selector on ALL data before splitting – the test set’s mean/variance, its missing-value distribution, and its label-feature correlations all leak into training ✓.
- Correct per-fold: split first; fit scaler, imputer, selector on the training fold only; transform the validation fold with those fitted objects ✓.
- The status code: a feature whose provenance is post-outcome – the data card’s provenance column catches it before any split ✓.
- Unequal folds: fold accuracies weight small folds equally – pool TP/FP/FN/TN across folds and compute metrics on the pooled counts (or weight by fold size) ✓.