

Exercise walk-through

5.2


Lists, stacks and queues

University Computer Science

Lists, stacks and queues: which end is cheap

- 1 **Layout** A Python list is a contiguous **array** - index i computes the address; a **linked list** chains nodes, splicing cheaply but walking to index.
- 2 **Amortise** Doubling regrows make append amortized $O(1)$; n front inserts move $\Theta(n^2)$ - the count quadruples when n doubles.
- 3 **Trace** push 3, 7, 1 then pop, pop returns 1 then 7 (last in, first out); enqueue a, b, c then two dequeues return a then b.

Array and linked layouts



One contiguous block with computed addresses versus nodes chained by pointers; the **stack** and **queue** differ only in which ends they use.

Exercises 2.1·2.2

2.1 push 4, push 9, push 2, pop, push 7 – give the two pops that a further pop, pop returns. [3]

2.2 State the number of element moves for n front-inserts into an initially empty array, as a formula and at $n = 200$. [3]

Exercises 2.1-2.2

2.1 push 4, push 9, push 2, pop, push 7 – give the two pops that a further pop, pop returns. [3]

2.1

- The pop removed 2; the stack reads 4, 9, 7 (bottom to top) ✓.
- The next pops return 7 then 9 ✓.

2.2 State the number of element moves for n front-inserts into an initially empty array, as a formula and at $n = 200$. [3]

2.2

- Moves = $n(n + 1)/2$ ✓.
- At $n = 200$: $201 \times 100 = 20\,100$ ✓.

Exercises 2.3-3.1

2.3 Enqueue x , y , z , dequeue twice – name the front element.

[3]

3.1 A queue is built on a Python list using `append` for enqueue and `pop(0)` for dequeue.

State the cost class of each operation and of n paired enqueue-dequeue rounds. Rebuild it on `collections.deque` and state both costs again. Give the total class ratio between the two designs at $n = 10^4$, with the reason the list version loses.

[8]

Exercises 2.3-3.1

2.3 Enqueue x , y , z , dequeue twice – name the front element.

[3]

2.3

- z ✓.
- Dequeues removed x then y , leaving z at the front ✓.

3.1 A queue is built on a Python list using `append` for enqueue and `pop(0)` for dequeue.

State the cost class of each operation and of n paired enqueue-dequeue rounds. Rebuild it on `collections.deque` and state both costs again. Give the total class ratio between the two designs at $n = 10^4$, with the reason the list version loses.

[8]

3.1

- List: enqueue $O(1)$ amortized; `pop(0)` slides all residents, $O(n)$ ✓.
- n rounds on the list: $\Theta(n^2)$ ✓.
- Deque: both ends $O(1)$; n rounds $\Theta(n)$ ✓.
- Ratio at $n = 10^4$: quadratic versus linear – the list moves about $10^8/2$ elements where the deque moves none per pop ✓.

Exercise 3.2

3.2 The bracket validator pushes opening brackets and matches each closer against the top of the stack.

Trace the scan of { [] () } listing the stack after each character. Trace ([)] and name the character and the mismatch that fails. State the empty-stack case and why it also fails.

Exercise 3.2

3.2 The bracket validator pushes opening brackets and matches each closer against the top of the stack.

Trace the scan of { [] () } listing the stack after each character. Trace ([)] and name the character and the mismatch that fails. State the empty-stack case and why it also fails. [7]

3.2

- { [] () }: after { $\rightarrow$ {; [$\rightarrow$ { [;] pops [; ($\rightarrow$ { (;) pops (; } pops { – empty at the end: balanced ✓.
- ([)]: stack after ([; the) finds [on top – mismatch at) (expected]) ✓.
- A closer arriving at an empty stack fails: nothing to match ✓.