

1.7 Friction

Name: _____ Class: _____ Date: _____

Total: 23 marks**KEY WORDS** friction • impending slip • static • kinetic

Objective

Decide whether friction holds, and with how much force it actually acts; solve impending-slip problems with correct direction reasoning; and compare tipping against slipping for a pulled or pushed block.


1 Key knowledge and worked examples

■ Friction takes what it needs

Before sliding, dry **friction** adjusts itself to maintain equilibrium, up to $F \leq \mu_s N$ – and while sliding, $F = \mu_k N$ opposes the motion. The inequality is the whole subtlety: the acting friction is whatever equilibrium demands, never automatically μN .

Worked example. A 50 kg block on a 20° incline ($\mu_s = 0.4$). Down-slope weight component: $490.5 \sin 20^\circ = 167.8$ N. Available friction: $0.4 \times 490.5 \cos 20^\circ = 184.3$ N. Since $167.8 < 184.3$ the block stays – and the friction actually acting is 167.8 N, not 184.3 N.

The reaction tilts at most $\arctan(\mu)$ from the normal



■ Tipping versus slipping

A block pulled horizontally at height h leaves the ground two ways:

- **Slips** when $P = \mu_s W$.
- **Tips** about its leading edge when $P \cdot h = W \cdot b/2$ (b = width along the pull).

The smaller threshold happens first. A tall, narrow, lightly-pulled crate tips; a low, wide, strongly-pulled one slides.

Worked example. $W = 400N$, $b = 0.8m$, $\mu_s = 0.4$, pull at $h = 1.2m$. Slip: $P = 0.4 \times 400 = 160N$. Tip: $P = 400 \times 0.4/1.2 = 133.3N$. It tips first – the pull is too high.

■ Direction before magnitude

At **impending slip**, friction opposes the *would-be* motion. A block being pushed up an incline feels friction down the slope; a ladder foot tending to slide outward feels friction pointing back under the ladder. State the would-be motion in words first – the sign convention then writes itself.

2 Practice

2.1 A 40 kg block rests on a level floor with $\mu_s = 0.35$. A horizontal 100 N push is applied. Will the block move? Give the friction force actually acting. [3]

2.2 A crate weighs 400 N, is 0.8 m wide and is pulled horizontally at a height of 1.2 m. With $\mu_s = 0.4$, find both thresholds and state which occurs first. [5]

2.3 A 200 N block is pushed up a 15° incline (parallel to the slope) with $\mu_s = 0.30$. Find the normal force, and the push needed to hold it in impending motion up the slope. [3]

3 Exam-style questions

3.1 A uniform 600 N ladder leans against a smooth vertical wall. Its foot rests on a floor with $\mu_s = 0.35$. The ladder's own weight is the only load.

Express the wall force in terms of the lean angle θ by moments about the foot, then find the smallest θ at which the ladder does not slip. Verify that at $\theta = 60^\circ$ the available friction exceeds what is needed, and state the acting friction at 60° . [6]

3.2 Block A (20 kg) sits on block B (30 kg), which sits on the floor. The coefficient of static friction is 0.30 between A and B, and 0.25 between B and the floor. A horizontal force P is applied to A.

Find the maximum friction available at each interface, determine whether A slips on B or the pair slides together as P grows, and give the value of P at which motion first occurs. Verify by checking the force transmitted to B against its floor friction. [6]
